

APR 25 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
ONTONAGON  
(County)

Located In:

Corner Code ##

1. Public Land Survey T R  
T R  
T R  
T R
2. Property Controlling S 9 T 46N R 39W #1  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

Recorded April 12 1994  
at 1:05 o'clock P M in  
Lib 3 page 192  
J. D. Boehm  
Register of Deeds

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat  
5. Private Claims

West 1/16 corner, Sections 4, 9; T46N., R39W.

I, Richard L. Drahn, in a field survey on August 11, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:

Not established in original survey.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Established corner by single proportion on line between the N.W. corner and the North 1/4 corner of Section 9.

PEER GROUP

Approved

Earl W. Applekamp 4-07-94  
Ont Co Rep



- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

At the corner position and 6" below surface of a E-W county road I set a 2" diameter by 12" long concrete filled, galvanized iron pipe with a 3" brass cap stamped to read: T.46N., R.39W.; W 1/16; S. 4, S.9; 1993, R.L.S. 21564. From which I established the following N.W. blazed and scribed bearing trees and reference objects:

Wisconsin-Michigan Power Co. Pole	#88-24849	S.15°W.	33.54 feet
10" Spruce	N.01°W.	41.71 feet	
8" Balsam	S.51°W.	78.65 feet	

A 6' steel sign post N.02°E., 20.72 feet

A standard 30" long, aluminum R.M. with a 3 1/4" aluminum cap, stamped to indicate true corner position bears North, 20.18 feet.

Signed by Richard L. Drahn Date February 10, 1994

Surveyor's Michigan License No. 21564

U.S.F.S. E-10