

APR 2 5 1995

		DRNER RECORDATION	CERTIFICATE		
COMMISSI For corners in	ON Filing Re	equirement of Act 74, M	ich. P.A. 1970	, .	
ONTONAGON			. I Rec	orded APvil 12	1994
(County)	Located In:	Corner Code ##	at_	1-10 o'do	
			Libe) 3 page	194
Public Land Survey	TR_ TR_		$- \mid \rightarrow$	Register of Deods	enn
	TR_	- (43)	- 0	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	T 0				
2. Property Controlling	S_9_T_46NR_3		_		
in Section	S T R				
3. Miscellaneous Property in Sec.	S T R S T R		— Regi	ister of Deeds Stamp &	File Number
r roporty in GCo.	<u> </u>		\ <u></u>		
	, Recorded Plat			ABCDEFG	нике
5. Private Claims					
Angle Point #1	Corner, Sections 4,	9; T46N, R39W.		3 3 4 4	_311
				4 7 8 8	
, Richard L. Drah	n , in a field survey on	<u> August 11, ı</u>	9 <u>93</u> ,	5	Ĭ Ï
do hereby certify that under	r requirements of P.A. 74, Michiga	an P.A. of 1970, the corner point	is mentioned	6 18 17 16	_151413
	re in conformance with regulation structions of the United States		•	7	
	of a Court of Law and/or that the	The state of the s		8 19 20 21	_222324
	e with the rules of the Michigan E d, re-established, monumented			9	
expressed below:	• '			10 30 29 28	_272625
	4 corners, all in the same to	own and range, may be rec	ordeđ	11	++++
on this certifica	ate.			12 31 32 33	-3'43'53'6
A. Description of origin	nal monument and accessori	es and/or subsequent rest	oration:	13 []	
· -					
Not establis	hed in original surv	ey.			
	•				
B. Description of corne	er evidence found and/or me	thod applied in restoring o	r reestablishing	corner:	
Corner set a 1 (000 feet East of 1/4	corner and on the	continu lin	a common to Croti	inn- 490
Corner sec a 1,0	000 1661 5021 01 1/4	corner and on the	section in	e common to Secti	ions 4&9.
				Market	PANALA.
				Service Of	用ICH/Mh
	PEER GROUP	Approved	!	A Same	A A MA
	٨ ١	Approved	'	RIGH	1
	Sail W Caro	lokano 4-07-	94	LAI	ŧ ^ 72.
		0	· · · · · · · · · · · · · · · · · · ·	SURV N) " S
·	Out 6 Res	p		AL COX	664
	W/02 -0 /-09				West of the second
				WWW.	HD
C. Description of monu	ument for corner and access	ories established to perpet	uate locating the	e position of the corner	3664
At the corrier by	nzirion i zer a zran	uaru z urameter by	50" Tong Si	piit base alumint	JM1
1993: R.I.S. 21	31" aluminum cap st 564: from which I e	amped to read: 140 stablished the foll	N., KOSW.; /	M.P. I; S. 4, S. Tazod and scribor	9; i
	nd/or reference obje		owing new b	iazea ana scribec	,
-	, <u>.</u>				
6"	Red Oak	N.50°W.	16.42 fee		
8"	White Birch	N.74°E.	30.75 fee	t	
Wisconsin_Mic	higan Power Co. Pole	#78_1300	S.25°W.	7.97 feet	
	gn post bears:		S.35°E.	1.15 feet	
5 5000, 51	J. P. 2.2 DOWI D.		J.00 L.	1.10 (000	
^	Λ ,, Λ				
Signed by Richard	L.E. Wraln	D.	ate <u>February</u>	y 10, 1994	
Surveyor's Michigan Lic	ense No21564		tanti iman	VED BY MICHIGAN STATE BOARD OF LA	NO SURVEYORS, JAN. 28, 19
-	11-12		FORM AFPHU	THE DI MINIMAN WHILE SOME OF LA	REVISED MAY 14, 19 REVISED JAN., 19
- · · · · · · · · · · · · · · · · · · ·					HELIOTA AUST. 13