

**SURVEY &  
REMONUMENTATION**

APR 29 1996

COMMISSION

**LAND CORNER RECORDATION CERTIFICATE**

**Filing Requirement of Act 74, Mich. P.A. 1970**

JUDITH D. ROEHM  
Ontonagon County  
LC 3/ 328 JEM Fee: 9.00  
Page 1 of 1

For corners in

<u>Ontonagon</u> (County)		Located In:	Corner Code ##
1. Public Land Survey	Sec. 4	T <del>48N</del> R <del>42W</del>	<del>48N 42W</del>
		T <del>48N</del> R <del>42W</del>	<del>48N 42W</del>
	OTHER	T 48N R 42W	# 008 pm
		T <del>48N</del> R <del>42W</del>	<del>48N 42W</del>
2. Property Controlling	S	T	R
in Section	S	T	R
3. Miscellaneous	S	T	R
Property in Sec.	S	T	R

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_
- Meander corner common to Sections 4 and 9, T48N, R42W

I, John R. Garske, in a field survey on September 7, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law: established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

- On August 9, 1848, Austin Burt set a cedar post from which a 12" maple bears S59°W, 13 links and a 12" Y. birch - N70°E, 10 links.
- 1915 - Plat of Valhalla
- 1941 a 4" concrete monument with 3 1/2" brass cap set by the Michigan Conservation Department Surveyor, Greg Shadko, RLS, and recovered by the Coleman Engineering Company on September 1, 1995.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

I accepted the found corner as described above, due to its longevity and its use in several surveys of record over the years. The brass capped monument was pointed out to us by Earl Applekamp, RLS, who has used it in several local surveys.

Information from Steve Szyzkoski, RLS, MDNR Surveyor, noted monument set in 1941 in a Public Fishing Site Survey by Greg Shadko, RLS. The location of the monument checks with Shadko's notes and map which refers to the Plat of Valhalla, and I am accepting it as marking the true corner position.

Corner Record Research on file with the Register of Deeds.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

The corner is marked by a 4" concrete monument with a 3 1/2" diameter brass cap stamped: Michigan Conservation Department; Public Fishing Site; 66-1; 1941; T48N, R42W; 4; M.C., from which I established the following bearing trees and/or reference objects:

- 5" ash - S60°W - 17.73 feet
- 16" ash - S81°E - 32.85 feet
- 8" willow - N54°E - 14.32 feet
- 6 foot steel rail with sign - N13°W - 1.03 feet

Signed by John R. Garske  
Surveyor's Michigan License No. \_\_\_\_\_

Date 9-19-95

