

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF:-	LOCATED IN:-	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 51 N. 37 E.	J7, I7, K1, G1
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19 , established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- Corner J7: Original monument and accessories not found. Found 1" I.D. iron pipe 2 ft. above ground.
- Corner I7: Original monument and accessories not found. Found 1" I.D. iron pipe 1 ft. above ground.
- Corner K1: Original monument and accessories not found. Found 1" I.D. iron pipe 30" above ground.
- Corner G1: Original monument and accessories not found. Found 1" I.D. iron pipe 6 ft. long.
- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:(east and west)
- Corner I7: Re-established 5-25-76 at pipe. Pipe fits with land calls/and has been used for many years as corner.
- Corner K1: Re-established 5-18-76 at pipe. This pipe set from original bearing tree seen by William Waara May 9, 1945.
- Corner J7: Re-established 5-25-76 at pipe. Pipe fits with land calls and has been used for many years.
- Corner G1: Re-established 5-18-76 at pipe. This pipe fits good with other corners in area and has been used for many years.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- | | |
|----------------------------------------------------------|----------------------------------------------------------------------|
| <u>Corner J7</u> : 1" I.D. iron pipe 2 ft. above ground. | <u>Corner K1</u> : 1" I.D. iron pipe 30" above ground. |
| 5" Sugar N11°W 26.6 ft. ¼S, NBT | 9" Maple N25°W 25.7 ft. S35, NBT |
| 10" Sugar S30°W 15.8 ft. ¼S, NBT | 10" Maple N49°E 45.2 ft. S36, NBT |
| <u>Corner I7</u> : 1" I.D. iron pipe 1 ft. above ground. | Power Pole S02°W 41.8 ft. S2 |
| 6" Sugar S21°W 13.9 ft. S22, NBT | |
| 4" Maple S76°E 14.7 ft. S23, NBT | |
| 3" Sugar N16°W 9.9 ft. S15, NBT | |
| | <u>Corner G1</u> : Set 1" I.D. x 36" iron pipe with 4" aluminum cap. |
| | 9" Sugar N83°W 22.4 ft. S33, NBT |
| | 10" Sugar N11°E 28.4 ft. S34, NBT |
| | Power Pole South 42.4 ft. |

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE June 28, 1976
CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
 REVISED MAY 14 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

