

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Form with fields for Ontonagon (County), Located In, Corner Code #, and sections for Public Land Survey, Property Controlling in Section, Miscellaneous Property in Sec., Lot No., and Private Claims.

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Stephan J. Szyszkoski, in a field survey on 08/10/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 3) Center-West 1/16 corner, Section 3. Not previously monumented.

(3-Sec. 3) North 1/16 corner between Sections 3 and 4. Not previously monumented. The US plat shows 1/4 corner 20.00 chains south and Section corner 20.10 chains north.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 3) Established the position for the corner midway and on a straight line between Quarter corner 1359.84' west and the Center of Section 3 1359.84' east.

(3-Sec. 3) Established the position for the corner on a straight line between 1/4 corner 1312.77' south and Section corner 1319.33' north, proportionate to the original record.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 10" Sugar N21°E 28.75' mrkd "1/16S BT" 17" Maple S53°E 20.9' do 4" Sugar S25°W 9.9' do 4" Sugar N77°W 17.3' do Set sq'd cedar post adjacent. E= 7848219.585 N= 230990.284

(3) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 4" Sugar S87°E 21.75' mrkd "1/16S BT" 6" Sugar S46°E 29.1' do Sugar in clump of 3 S69°W 9.5' do 5" Sugar N41°W 20.9' do Set sq'd cedar post adjacent. E= 7847807.206 N= 231406.201

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID RL0593: N= 221669.506 m. E= 7868965.488 m.

Signed by [Signature] Date 08/26/2015 Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division