

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ontonagon Located In: Corner Code #
(County)
1. Public Land Survey T 51N R 37W F-13
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

SURVEY &
REMONUMENTATION

APR 07 1998

SECTION

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Joseph C. Domitrovich, in a field survey on November 24, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

(F-13) South 1/4 Corner of Section 33, T51N, R37W

A. Description of original monument and accessories and/or subsequent restoration:

1845 - Austin Burt set post
10" Cedar N 71° E 28 links
12" Birch N 39° W 30 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

At the corner, I found the intersection of three old fences, running North, West and East. Distance East to a stream crossing works very well with GLO. Distance West to the SW Corner of Section 33 also works well: 2640.0 - GLO, 2642.30' - Meas.

I accepted the fence intersection as the 1/4 Corner and have monumented it as such.

FEER GROUP REPRESENTATIVE

Earl W. Applekamp
COUNTY CLERK 12-01-97

Research on file with County Remonumentation Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 5/8" x 24" iron pin, driven at a fence intersection, with a 3" diameter aluminum cap stamped to read: COUNTY REMONUMENTATION; S. 33; 1/4; T.51N, R.37W; S.C.; 1997; P.S. 37273.

Witnesses:

12" Balsam West 14.01'
8" Maple N 10° E 29.75'
16" Spruce N 83° E 27.28'
Steel Sign Post South 0.61' (to face)



NOTE: Bearings are magnetic. Distances are to nail in side of witness objects unless noted.

Signed by J. C. Domitrovich Date 11/30/97

Surveyor's Michigan License No. 37273