

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Ontonagon  
(County)

Located In:

Corner Code #

1. Public Land Survey

T 51N R 40W

A-8 Same

T 51N R 41W

M-8 Corner

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

I, Joseph C. Domitrovich, in a field survey on June 4, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

(A-8/M-8) 1/4 Corner Common to Sections 19 and 24, T 51N, R40/41W

A. Description of original monument and accessories and/or subsequent restoration:

1845 - Austin Burt, D.S., set post

12" Hemlock N 09° W 22 links

14" Hemlock N 55 1/2° E 28 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Original corner and accessories have been destroyed by road construction. I re-established the corner midway and on line between section corners to the North and South. The corner works well with others in the area.

Research on file with County Remonumentation Representative.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 5/8" iron pin with a 3" diameter aluminum cap stamped to read: COUNTY REMONUMENTATION, T. 51N, R. 40W, R. 41W; 1/4; S. 24, S. 19; 1997; P.S. 37273. I also placed a reference monument (R. M.) to the East, a 2" x 30" aluminum pipe with a 3" diameter aluminum cap, stamped to indicate that the corner is West 37.06'.

Witnesses:

Power Pole S 78° E 37.52'

8" Ash S 32° W 56.49'

7" Red Pine N 39° W 32.92'

Reference Monument N 88° 02' 23" E 37.06'

NW Corner Sec. 19 N 00° 14' 12" E 2640.58'

SW Corner Sec. 19 S 00° 14' 12" W 2640.58'

NOTE: Bearings are magnetic. Distances are to nail in side of witness objects unless noted.

Signed by Joseph C. Domitrovich

Date 6/9/97

Surveyor's Michigan License No. 37273

PEER GROUP APPROVED

Earl W. Applekamp  
COUNTY REPRESENTATIVE 6-10-97

