

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

ONTONAGON CO.

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. <u>53N</u> S., R. <u>37W</u> E. W.		<u>E8, D7</u>
2. PROPERTY CONTROLLING IN SECTION_____ T. _____ S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION_____ T. _____ S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 1, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner E8: Original monument and accessories not found. Found 1" I.D. by unknown length iron pipe 30" above ground set by M. C. Larsen, 12-17-43, from original BT.

Corner D7: Original monument and accessories not found. Found 3/4" I.D. Iron pipe 15" above ground level set by M.C. Larsen, 8-24-55, from original BT.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner E8: Restored at iron pipe.

Corner D7: Restored at iron pipe.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner E8: 1" I.D. by unknown length iron pipe 30" above ground level.

18" Hemlock	S37°E	3.7 Ft.	1/4 S, NBT
16" Hemlock	S87°W	1.5 Ft.	1/4 S, NBT
14" Sugar	N05°W	11.0 Ft.	1/4 S, NBT

Corner D7: 3/4" I.D. x unknown length iron pipe 15" above ground level.

22" Sugar	N58°E	6.9 Ft.	1/4 S, NBT
12" Sugar	S10°W	2.8 Ft.	1/4 S, NBT
5" Sugar	N11°W	13.3 Ft.	1/4 S, NBT

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY Keith L. Sackett DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY  
MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett

Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

