

**1999 PRESQUE ISLE COUNTY, STATE OF MICHIGAN,
LAND CORNER REMONUMENTATION**

LIBER 335 PAGE 219

DEC 29 1999

SECTION

**LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in
PRESQUE ISLE

(County)

Located In:

BISMARCK TWP.

Corner Code #

MPOST

1. Public Land Survey

T 34 N R 4 E

12 ✓

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

S T R

Recorded

Dec 20, 1999

At 10:30 o'clock A M

Janet M. Lamb
Reg. of Deeds, Presque Isle Co. MI

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, James A. Beck, in a field survey on Dec 1, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

Meander Post on line Secs 29 and 30 on N. Shore of Lake Nettle
1856 G.L.O. by Alfred Miller
"8.75 From Sec. Cor. in Lake - set Meander post"
Cedar 12 N17W 53; Cedar 8 N48E 45

July 10, 1990 Witness card furnished by Porter's Survey
* "NOTE: Not true meander corner, located North of true M.P." 539°W 3.90 12" Pine
553°E 21.98 16" Pine; N30°W 72.10 NE Cor. Cabin
"Fd. 1/2" rod 16' South to water"

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Meander Post on line Secs 29 and 30 on N. Shore of Lake Nettle
December 1, 1999 Remonumentation by James A. Beck P.S. 21559
Found 1/2" iron rod and P.S. 15410 cap; 539°W 3.90, 14" Pine
553°E 21.98 17" Pine
South 16' edge of water

Witnessed by Peer Group
in accordance with P.A. 345
Chairman William J. Dean
Date 12/14/99

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Meander Post on line Secs 29 and 30 on N. Shore of Lake Nettle
December 1, 1999 Remonumentation by James A. Beck P.S. 21559
1/2" iron rod and P.S. 15410 cap; 539°W 3.90, 14" Pine
553°E 21.98, 17" Pine; N30°W 72.10 NE Cor. Cement Block Cabin
N25°W 28.54' P.S. 21559 tag in 12" Spruce
South 16' edge of water



Signed by

Surveyor's Michigan License No. 21559

Date

12-18-1999