

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
PRESQUE ISLE
(County)

Located In

Corner Code #

- | | | | | |
|--------------------------------------|---------|--------------|-------------|-------------|
| 1. Public Land Survey | | T <u>36N</u> | R <u>4E</u> | <u>L-10</u> |
| | | T _____ | R _____ | _____ |
| 2. Property Controlling in Section | S _____ | T _____ | R _____ | _____ |
| | S _____ | T _____ | R _____ | _____ |
| 3. Miscellaneous Property in Section | S _____ | T _____ | R _____ | _____ |
| | S _____ | T _____ | R _____ | _____ |

Register of Deeds Stamp & File Number

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Carl T. Kiiskila, in a field survey on January 20, 1999 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	13		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:
L-10 FREDRIC LOUD REGISTERED CIVIL ENGINEER IN 1928 SET THE CENTER POST OF SEC. 25
WHILE DOING THE SUPERVISOR'S PLAT OF SACRED ROCK PARK RECORDED IN LIBER 1 PAGE 125.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:
L-10 FOUND A 3/4" ROD IN CONCRETE PRESUMED TO BE SET BY FREDRIC LOUD WHILE DOING
THE SUPERVISOR'S PLAT OF SACRED ROCK PARK.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
L-10 FOUND A 1/2" ROD IN CONCRETE
WITNESS: 20" W. PINE S85°E 14.35'
6" MAPLE N38°W 15.62'
8" MAPLE S55°W 19.35'
6" BALSAM S6°E 17.06'



Signed by:

Carl T. Kiiskila

Date:

2-2-99

Surveyor's Michigan License No.:

33981