

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED/FILED

For corners in **SAGINAW COUNTY REMONUMENTATION**

1997 SEP 26 P 3: 28

MILDRED M. DODAK  
REGISTER OF DEEDS  
SAGINAW COUNTY, MI.

LIBER 2027 PAGE 459

*Liber 7 Page 150*

Register of Deeds Stamp & File Number

SAGINAW Located in: B'RUN TWP. Corner Code #  
(County)

1. Public Land Survey T 10N R 6E G-13  
T      R       
2. Property Controlling S      T      R       
in Section S      T      R       
3. Miscellaneous S      T      R       
Property in Sec. S      T      R     

4. Lot No.             , Recorded Plat                       
5. Private Claims   

I, BRIAN D FERGUSON, in a field survey on JUNE 17, 19 97 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5			4			3		2	
3													
4	7			8			9			10		11	
5													
6	18			17			16			15		14	
7													
8	19			20			21			22		23	
9													
10	30			29			28			27		26	
11													
12	31			32			33			34		35	
13													

A. Description of original monument and accessories and/or subsequent restoration:

G-13: WOOD POST SET BY WAMPLER IN 1822

APPROVED BY PEER GROUP  
P.A. 345 OF 1990  
SAGINAW COUNTY

*9-18-97 BDF*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-13: FOUND 1/2" IRON PIPE  
LCRC RECORDED IN L 2 PG 127  
RECORDED SURVEYS L 1376 PG 206

ACCEPTED BY THE PEER REVIEW GROUP AS THE BEST  
AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-13: SET 5/8" ROD W/3" BRASS CAP IN MONUMENT BOX  
EAST 38.15' "T" IRON IN PVM'T (G-1, T9N-R6E)  
NORTH 7.20' EDGE OF PAVEMENT  
S40E 47.55' NAIL & TAG IN FCE GATE POST  
SOUTH 11.70' EDGE OF PAVEMENT

SURVEY &  
REMONUMENTATION

MAR 18 1998

SECTION

Signed by Brian D Ferguson  
Surveyor's Michigan License No. 26454

Date SEPTEMBER 25, 1997

