## APPROVED BY PEER GROUP P.A. 345 OF 1990

COMM

## LIBER 1986 PAGE 473

	P.A. 345 OP 1990	
	SAGINAW COUNTY	
2	-7-9/1	

SAGINAW COUNTY REMONUMENTATION

8-7-90	LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970
For corners in	Filing Requirement of Act 74, Mich. P.A. 1970
	Located in: Thomas Twp. Corner Code #
Saginaw (County)	Ocaled III. Montage 7119
1. Public Land Survey	Filing Requirement of Act 74, Mich. P.A. 1970  SACHED REGISTER  T 12N R 3E
2. Property Controlling	S T R
in Section	S_T_R_ Sher 7 Page 63
3. Miscellaneous	STR
Property in Sec.	SI
4. Lot No, Reco	orded Plat
5. Private Claims	
	3 <del>                                     </del>
	4 - 7 - 8 - 0 - 10 - 11 - 12 - 1 - 10 - 11 - 12 - 1 - 10 - 11 - 12 - 1 - 10 - 11 - 12 - 1 - 12 - 1 - 12 - 12
I. Brian D Ferguson, In a fle	Id survey on September 3, 19 96 do hereby state that under in P.A. of 1970, the corner points mentioned in lines 1 and 2 above
were in conformance with regula-	tions and futes tribute to be browner Ruredu of Land Management or by a
decree of a Court of Law and/or	that the corner points increases a part of B - 10 - 20 - 21 - 22 - 23 - 24 - 22 - 23 - 24 - 22 - 23 - 24 - 24
Law; established, re-established,	monumented, recovered, found as expressed below:
	orners, all in the same town and range, may be recorded
NOTE: Not more than 2 con this certificate.	11
	12 31 32 33 33 35 36
	13
A. Description of original	monument and accessories and/or subsequent restoration:
Lo Mond nost set	by Wampler, 1822.
I-8 Wood post set LCRC L. 2, Pg.	
	13, Pg. 1194; L. 1681, Pg. 416.
Agrees with SC	CRC witnesses, 1976.
	evidence found and/or method applied in restoring or reestablishing corner:
B. Description of corner	evidence found and/or metriou applied in restoring of the same of
	i
I-8 Found 3/4" pig	pe in monument box.
Accepted by p	peer group as best available evidence of original corner.
;	•
C. Description of monu	ment for corner and accessories established to perpetuate locating the position of the corner:
	act of Holl
	bar with Saginaw County Remon. cap.
<u>.</u>	60 N & S W face power pole.
S50°W 88. N50°E 98.	. In cond Caldian Donal
N50°E 98. No°E 27.	D TO NA. INC.
1402 27.	
//	11) Y
Signed by Decoe	n) N tordeson Date 9-27-90
	nee No. 96454
Surveyor's Michigan Lice	1196 1/01
B. The same of the same	FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983
MAY 1 CO	REVISED OCT., 1995