API	PROVED BY PEER GROUF P.A. 345 OF 1990 SAGINAW COUNTY	SAGINAW COU	925 PAGE 1167 INTY REMONUMENTAT RECORDATION CERTIFICA	TION Spher 6	Page	291
12	2-7-94/20		RECORDATION CERTIFICA ent of Act 74, Mich. P.A. 19		DEC.	
	corners in SURVEY &	ring nequirem	ent of Act 74, Mich. P.A. 19	Om E	£ 29	200
	REMONUMENTATION	cated In:	Corner Code ##	Series Series	,; }	26 kg
1.	Public Land Survey	T <u>12N</u> R <u>4E</u> T R	K-13	ALMID 30 VD X	9 30/	RECORDED & F
		T R		500	7	FILED
9		T R T R		, in the second	32	a
		r R				
		T R T R		Register of Deeds Stam	p & File Num	ber
	rioperty in Sec. S	' N				
	Lot No, Recorded Pla			— ABCDEF	GHIJ	KLW
5.	Private Claims	· · · · · · · · · · · · · · · · · · ·		2 6 5 4	3 2	
		4		3		
	Duane F. Ledy , in a field si	unyay on July 28	10 94	4 7 8 9	10 -11	
	ereby certify that under requirements of F	P.A. 74, Michigan P.A. of 1	970, the corner points mentioned	6 18 17 16	15 14	
curre	ies 1 and 2 above were in conformance ent manual of survey instructions of the	United States Departmen	nt of the Interior, Bureau of Land	7	T I	
	agement or by a decree of a Court of Law e were in conformance with the rules of			8 19 20 21	22 23	24
Cour	t of Law; established, re-established			9	++++	
	essed below: E: Not more than 4 corners, all in	the same town and	range may be recorded	10 30 29 28	27 26	25
,101	on this certificate.	i tite same town and i	ange, may be recorded	12 31 32 33	34 35	36
_				13		
Α.	D. Hammond survey in 1978 L1558 P933.	-13, J.Wampler, 1822. ey maps show position records witnesses from the shows K-13 as a found th	of monument at 3.53' west of K- n K-1 (T11N, R4E) to K-13 as we nd 2" iron in monument box: L16	est 37.0' (apparently sho	uld be 3.70')	
В.	Description of corner evidence foun <u>K-13</u> Found 2" City of Saginaw cas			ng corner:		
	Found witnesses in recorded N 45° E 34.73' to PK nail in F	instruments;	E 35.00').			
	Position of existing city monu	ment accented as hest	possible position of original con	ner		
	Position accepted by Saginav					
		e e				
C. 1	Description of monument for corner	and accessories esta	blished to perpetuate locating	the position of the corn	er:	
	K-13 Stamped top of existing 2" ca	st iron monument with	_			
	N 45° E 34.73' to PK nail in			TRIPE	E OF MICA	10000
	N 45° W 46.60' to PK nail in S 45° E 85.70' to PK nail in	utility pole.		7. V.	DUANE F.	27.
	S 45° W 47.58' top center of	fire hydrant operator n	out.	* 10030	LEDY PROFESSIONAL SURVEYOR NO. 21675	* #0/3/1/1
			·	"Ini	POFESSIONAL	211918
	-1	7/2		10.1.	-,) 6011	
Sign	ed by	Juds.	Date	(Kusmver !	1114	
Surveyor's Michigan License No. 21575 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983						