

NOV 2 1 1997

LIBER

2 PAGE 119

COMMISSION

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

97 SEP -9 AM 8:56

LIBER NO. 2 PAGE NO. 119
ESTHER LEE
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac

(County)

Located In:

Corner Code #

1. Public Land Survey

T10N R12E

B - 1

T R
T R
T R
T R

Seg. 2

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, John A Millettics, in a field survey on May 21, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO NOTES

No GLO's Available

APPROVED PEER BOARD MEETING

Aug 18, 1997 JN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B - 1

N 1/4 Cor Section 6 T10N-R12E

Found Monu Box - removed by Sanilac County Road Comm. during reconstruction of Road - REPLACED using Act 74 recorded Liber 1 Page 387

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B - 1

N 1/4 Corner Section 6 T10N-R12E

Moun Box with iron and cap

South 55.00 feet to a 1/2" Iron Bar

South 31.30 feet to a nail in a Tele Pole

N05°E 55.20 feet to a nail in a Fence Post

S30°E 60.75 feet to a nail in a Fence Post

N50°E 59.80 feet to a nail in a 12" Ash

N10°W 39.00 feet to a nail in a 10" Ash

East 2659.00' to the NE Cor. Section 6

West 2829.72' to the NW Cor. Section 6

Signed by John A Millettics

Surveyor's Michigan License No. 25859

Date Aug 11, 1997

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

