

LIBER 1 PAGE 386

SURVEY &
REMONUMENTATION CORNER RECORDATION CERTIFICATE

NOV 19 1993

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF:-	LOCATED IN:-	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 10 N. R. 12 E.		(1-1, H-1)
2. PROPERTY CONTROLLING IN SECTION _____ T. _____ N. S. R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. S. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

RECEIVED FOR RECORD

93 NOV -4 AM 11:58

LIBER NO. 1 PAGE NO. 386

ESTHER LEE
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, John A. Millettics, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 5, 1993, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

I - 1 Found R/R spike in place as recorded in Liber 3 Page 485 of the Sanilac County Records.

H - 1 Found hex bolt in blacktop varied by survey dated 7-27-88

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I - 1
NE Cor Section 3 T10N-R12E
Found Monu. Box

H - 1
N 1/4 Cor Section 3 T10N-R12E
Found Hex Bolt

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I - 1
NE Cor Section 3 T10N-R12E
Monu Box Set
S45°W 58.10' to a nail in a Power Pole
S45°E 43.90' to a nail in a Power Pole
N70°E 49.90' to a nail in a 30" Elm

H - 1
N 1/4 Cor Section 3 T10N-R12E
Monu Box Set
South 56.95' to a nail in a 18" Maple
S45°E 47.15' to the West end of a 12" Driveway Culvert.

Distance between I - 1, H - 1 measures 2595.56 feet

SIGNED BY John A. Millettics DATE Nov 1, 1993

SURVEYOR'S MICHIGAN REGISTRATION NO. 25859

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

