

JAN 19 2000

LIBER

2 PAGE 359

RECEIVED FOR RECORD

99 NOV 30 AM 9:04

SECTION

1999 REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER NO. 2 PAGE NO. 359
NICHELE VANHORMAN
REGISTER OF DEEDS
SANILAC COUNTY, MICHIGAN

For corners in

SANILAC

(County)

Located in:

Corner Code #

1. Public Land Survey

T11NR 16 E A-3

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, John A. Milletics, in a field survey on Aug. 2, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-3 Hemlock 12 S15W 20 1/2; Birch 10 N11W 31
Old Survey Liber - None
L.C.R.C. - None
Act 132 - Liber 2 Page 497
Unrecorded survey = Milletics Dated Aug 1994

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-3

SW Corner Section 6, T11N-R16E
Found 5/8" Iron bar in gravel road bed 3'± west of centerline
North 2650.40 feet to the W 1/4 Corner Section 6
South 2649.00 feet to the W 1/4 Corner Section 7
Accepted as best evidence

APPROVED PEER BOARD MEETING
NOV 19, 1999

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A - 3

SW Corner Section 6 T11N-R16E
5/8" Iron Bar in Gravel Road Bed
North 2650.40 feet to the W 1/4 Corner Section 6
South 2649.00 feet to the W 1/4 Corner Section 7
S45°W 33.85 feet to a Stop Sign
S60°E 73.50 feet to a nail in a Power Pole
N45°E 42.85 feet to a Stop Sign

Signed by

Surveyor's Michigan License No. 25859

Date 11-15-1999