

JAN 22 2001

LIBER 3 PAGE 75

RECEIVED FOR RECORD

00 DEC -1 AM 9:33

2000 REMONUMENTATION PROGRAM  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER NO. 3 PAGE NO. 75  
MICHELE VANNORMAN  
REGISTER OF DEEDS  
SARASOTTA CO., MICHIGAN

SECTION

For corners in

Sanilac

Located in:

Corner Code #

(County)

1. Public Land Survey

T 11N R 16E

E - 7

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

2000

John A Millettics, in a field survey on May 1, 1983, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Description of original monument and accessories and/or subsequent restoration:

E - 7

SE Corner Section 17 T11N-R16E

GLO Notes

Pine 28" S34°E 30 Links

Beech 12" N49°W 47 Links

Act 132 - Liber 3 Page 133 -

L.C.R.C. Forms - none

Unrecorded surveys - Millettics July 1983

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E - 7

SE Corner Section 17 T11N-R16E

Found 1/2" Iron Bar in gravel road bed

West 2664.04 feet to the S 1/4 Corner Section 17

East 2658.64 feet to the S 1/4 Corner Section 16

Accepted as best evidence

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E - 7

SE Corner Section 17 T11N-R16E

1/2" Iron bar in gravel road bed

N55°E 61.33 feet to a nail in a Power Pole

N45°W 45.95 feet to a nail in a Power Pole

S45°W 34.40 feet to a Stop Sign

S55°E 66.53 feet to a nail in a Power Pole

West 2664.04 feet to the S 1/4 Cor Section 17

East 2658.64 feet to the S 1/4 Cor Section 16

APPROVED PEER BOARD  
MEETING NOV 25 2000

*gm*

igned by

Surveyor's Michigan License No. 25859

Date Nov 15, 2000