

JAN 22 2001

SECTION

LIBER 3 PAGE 70
2000 REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD
00 DEC -1 AM 9:33
LIBER NO. 3 PAGE NO. 70
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac Located in: Corner Code #
(County)

1. Public Land Survey T11N R 16E J - 7
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, John A Miletics, in a field survey on May 1, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	10	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

J - 7
S 1/4 Corner Section 14 T11N-R16E
GLO Notes
Ash Tree 9" N09°W 6 Links
Birch 9" S09°E 3 Links

Act 132 - None
L.C.R.C. Forms - None
Unrecorded surveys - Sanilac Land Surveying Jane 1977 - Milletics Dec 1988
Milletics April 1993 - Milletics May 1998

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J - 7
S 1/4 Corner Section 14 T11N-R16E
Found 1" Iron bar in gravel road bed
West 2703.88 feet to the SW Corner Section 14
Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J - 7
S 1/4 Corner Section 14 T11N-R16E
1" Iron Bar in gravel road bed
West 146.00 feet to the centerline of M-46
N05°E 26.50 feet to a nail in the west leg of camp sign
N40°E 27.75 feet to a nail in the east leg of camp sign
N60°E 30.25 feet to a nail in a 8" Cedar
N80°W 99.55 feet to a nail in a Light Pole - N10°W 22.40 feet to a Right of Way Marker
South 7.0 feet to the centerline of the gravel road
West 2703.88 feet to the SW Corner Section 14

APPROVED PEER BOARD
MEETING NOV 25 2000

Signed by John A Miletics
Surveyor's Michigan License No. 25859

Date Nov 15, 2000