

JAN 19 2000

LIBER

2 PAGE 355

SECTION

1999 REMONUMENTATION PROGRAM  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD  
99 NOV 30 AM 9:04

For corners in

SANILAC

(County)

Located In:

Corner Code #

1. Public Land Survey

T 12N R 16 E A-12  
T R  
T R  
T R  
T R

2. Property Controlling  
in Section

S T R  
S T R  
S T R  
S T R

3. Miscellaneous  
Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

I, John A. Milletics, in a field survey on Aug. 2, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-12 Hemlock 26 N49W 8; Beech 11 S17W 25

Old Survey Liber - None

L.C.R.C. - None

Act 132 - Liber 2 Page 601, Liber 2 Page 498

Unrecorded survey - Sanilac Land Dated July 1979, Milletics Dated Aug 1990

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-12

W 1/4 Corner Section 31, T12N-R16E

Found 1" Iron Bar 7'± west of gravel road centerline

North 2637.10 feet to the NW Corner Section 31

South 2657.22 feet to the SW Corner Section 31

Accepted as best evidence

APPROVED PEER BOARD MEETING  
NOV 19, 1999

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A - 12

W 1/4 Corner Section 31 T12N-R16E

1" Iron bar in gravel road bed

North 2637.10 feet to the NW Corner Section 31

South 2657.22 feet to the SW Corner Section 31

East 42.57 feet to a nail in a 24" Twin Ash

N30°E 85.29 feet to a nail in a 24" Poplar

S30°E 73.48 feet to a nail in a 12" Thorn Apple

East 33.00 feet to a 1/2" Iron Bar

Signed by

Date 11-15-1999

Surveyor's Michigan License No. 25859