

JAN 22 2001

LIBER

3 PAGE 42

SECTION

2000 Remonumentation Program
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

00 NOV 27 AM 8:56

LIBER NO. 3 PAGE NO. 42
MICHELE VANHORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac Located In: Corner Code #
(County)

1. Public Land Survey T12N R16E B - 7
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, John A Millettics, in a field survey on May 1, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
GLO Notes

Sugar 6" N01°E 14 Links
Beech 6" N51°E 30 Links

Act 132 - Irvin Chope Liber 2 Page 568, Sanilac Land Survey Liber 4 Page 261
Northwest Surveying Liber 4 Page 627
L.C.R.C. - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B - 7
S 1/4 Corner Section 18 T12N-R16E
Found 3/4" Iron Bar 1' Deep in Gravel Road Bed
West 2606.82 feet to the SW Corner
East 2606.82 feet to the SE Corner
Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B - 7
S 1/4 Corner Section 18 T12N-R16E
3/4" Iron Bar in Gravel Road Bed
South 10'± to centerline of gravel road bed
North 33.00 feet to a 1/2" Iron Bar with cap
N10°W 2.50 feet to the E. Leg of a Road Sign
S45°W 49.35 feet to a nail in a 12" Birch
S30°E 59.30 feet to the NW Corner of a Bell Riaser Box
West 2606.82 feet to the SW Corner
East 2606.82 feet to the SE Corner

APPROVED PEER BOARD
MEETING NOV 25 2000

Signed by John A Millettics
Surveyor's Michigan License No. 25859

Date June 4, 2000

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

