

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

96 MAY 15 AM 8:18

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T13N R 13E

C - 13 D - 13

T R

T R

T R

T R

2. Property Controlling in Section

S

T R

S

T R

3. Miscellaneous Property in Sec.

S

T R

S

T R

LIBER NO. 2 PAGE NO. 84
ESTHER LEE
REGISTER OF DEEDS
SANILAC CO. MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, John A Millettics, in a field survey on March 14, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C - 13 GLO Notes

Set Post at 80 Chains

NO Survey in Old Liber

B. Ash 20" N72½E 15 Links

NO Act 132 NO Act 74

B. Ash 12" N47W 40 Links

Road Comm Monu Box

D - 13 GLO Notes

Set Post 40 Chains

NO Survey in Old Liber

Hemlock 11" N67½W 25 Links

NO Act 132 NO Act 74

Hemlock 11" N44W 18 Links

Unrecorded survey I.E. Chope

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C - 13

SW Cor Section 32 T13N-R13E

Found Monu Box

APPROVED PEER BOARD MEETING
APRIL 30, 1996 gn

D - 13

S 1/4 Cor Section 32

Found R/R Spike in Gravel Road Bed

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C - 13

SW Cor Section 32 T13N-R13E

Monu Box

West 16.67 to a Monu Box

N40E 62.60 to SW Cor of a Bell Box

N45W 83.15 to a nail in a Power Pole

East 2641.74 feet to the S 1/4 Cor

West 2659.48 feet to the S 1/4 Cor

D - 13

S 1/4 Cor Section 32 T13N-R13E

1" Iron Bar

North 207.17 feet to a nail in a Power Pole

N05E 56.80 feet to a nail in a 6" Poplar

N07E 32.80 feet to a nail in a 6" Poplar

West 2641.74 feet to the SW Cor

East 2641.74 feet to the SE Cor



Date April 9, 1996

25859