

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

98 DEC -1 AM 9:10

LIBER NO. 2 PAGE NO. 273MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T14N R12E

B-13

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, John A. Milletics, in a field survey on Nov 1, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-13 GLO Notes - Maple 28 N64E 29; Birch 9 N29W 28
Old Survey Liber - Survey by M.E Ward dated 1899
L.C.R.C. - None
Act 132 - None
Road Comm - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B - 13 S 1/4 Cor Section 31 T14N-R12E
Set 1/2" Iron Bar at a proportional distance between
the SE Cor and the SW Cor of Said Section
East 2637.60 feet to the SE Corner Section 32
West 2135.03 feet to the SW Corner Section 32

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B - 13
S 1/4 Corner Section 31 T14N-R12E
1/2" Iron Bar with cap
South 6.20 feet to a nail in a 18" Ash Stump
S05°W 17.90 feet to a nail in a 18" Ash
S40°E 31.80 feet to a nail in a 12" Poplar
S85°W 24.80 feet to a nail in a 15" Poplar
West 75.00 feet to a Fence Corner intersection

APPROVED PEER BOARD MEETING
NOV 30, 1998

gm

SURVEY &
REMONUMENTATION

JAN 15 1999

SECTION

Signed by

John A. Milletics

Date Nov 20, 98

Surveyor's Michigan License No. 25859