
ST. CLAIR COUNTY, MICHIGAN **OFFICIAL GOVERNMENT CORNER**





LIBER 008 PAGE 90

	Filing Requirer	ment of Act /4, Mich. P.A. 19	170 CHIGH
	Located In:	Corner Code ##	8E 95
Public Land Survey	Clyde Twp. T7N. R16E. T. R	K-13	ESTATION OF PROPERTY OF PROPER
2. Property Controlling	T R S T R	JUN 2.	
in Section	\$ T R	Deg. 2	
3. Miscellaneous	S T R		Register of Deeds Stamp & Mie Number
Property in Sec.	S T R		· · · · · · · · · · · · · · · · · · ·
	Recorded Plat		A B C D E F G H I J K L
5. Private Claims			_ 2
			- [- [-] -] - [-]
			3
Daniel E. Jol		5, 95	4 7 7 8 9 9 10 11 12
	, in a field survey on quirements of P.A. 74, Michigan P.A. of		5
in lines 1 and 2 above were in current manual of survey instr Management or by a decree of above were in conformance with Court of Law; established, expressed below:	n conformance with regulations and uctions of the United States Departm a Court of Law and/or that the corner part that the rules of the Michigan Board of the re-established, monumented, re-monagements of the Michigan Board of the Michigan Board of the re-established, monumented, re-monagements of the Michigan Board of the re-established.	rules therefore as required in the tent of the Interior, Bureau of Land points mentioned in lines 3, 4 and 5 Land Surveyors or by a Decree of a prumented, recovered, found as	6 18 17 15 15 14 13 7 8 19 20 21 22 23 24 9 10 30 29 28 27 26 25
NOTE: Not more than 1 co	orner, may be recorded on this (certificate.	11
			12 31 32 34 34 35 36
A man fat fatalists		eubanaught rostoration:	13
A. Description of original n	nonument and accessories and/or	subsequent restoration.	
			STATE PLAIN COORDINATES
ון משמון	07 PAGE 365		
D Madid	// FAGE 303		N
,			E
	vidence found and/or method appli	ad in restoring or reestablishing c	DANIEL E. JOHNSON LAND SURVEYOR 13754
			Mark the second of the second
			MILLOFO LAND
0 0 10		hilahad sa maunas, was a lagasima sha	position of the corner:
Set 1/2" x 18"	ont for corner and accessories esta Rerod with 2" dia. alum		. Clair County Official
Corner with ma	•		
	in center of south boun	d lane of existing Nor	th Road pavement.
Located on the	True Township line.	_	-
N 25°E 90.53	' to set PK nail w/coun	ty remon tag in E side	of power pole
N 85°E 98.83	' to set PK nail w/coun	ty remon tag in S side	of power pole
S 65°W 212.11	' to set PK nail w/coun	ty remon tog in C side	or bower bore
S 40°W 224.03	to set DV neil w/com	ty remon tag in 5 side	or bower bore
WEET 7570 501 1	' to set PK nail w/coun	ty remon tag in N side	of power pole
	o S 1/4 corner of Secti		
EAST 2032,43' t	o S 1/4 corner of Secti	on 36, T7N-R16E	
	$\nabla \cdot 0$! (\ 0 \	Marz 26 1005
Signed by	- Love	Date _	May 26, 1995
	Daniel E.	Johnson	
Surveyor's Michigan Licens	se No		PA 345-1990
·	¥15/54		PEER COMMITTEE
			TELL COMMITTEE
ADDDOVED AS AN OFFICE	NAL COVERNIATING CONTROL	ZET OLAD COLUTY	APPROVED 6-10-94 JA
APPROVED AS AN OFFIC	CIAL GOVERNMENT CORNER BY	JI. CLAM COUNTY:	
Signed By:	(_)nain	I huson	7-31-95
· · · · · · · · · · · · · · · · · · ·		Johnson	Date
or. Gall Oc	, grantul die	odilisy i	5000
Sunyoyar's Michigan Licens	se No.		0.5

Surveyor's Michigan License No.