

SCHOOLCRAFT COUNTY PEER GROUP APPROVED

SURVEY &
REMONUMENTATION

JAN 21 1999

DATE 10/21/98 JOB LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION _____

For corners in

<u>Schoolcraft</u> (County)	Located In:	Corner Code #
1. Public Land Survey	<u>T41N R16W</u>	<u>A-5</u> ✓
	<u>T41NR17W</u>	<u>M-5</u>
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____

SIGRID HEDBERG 1P
SCHOOLCRAFT CO. REGISTER
Page 1 of 1 LC 4/ 210
JLO Rec. Date 12/03/98 Time 14:26
REVENUE FEES: 9.00

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5	X												
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Thomas P. O'Brien in a field survey on Oct. 23, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A5 NW Corner Section 18, T41N - R16W
July 29, 1845 - John Burt D.S. set post corner common to sections 7 & 18
T41N - R16W and sections 12 & 13, T41N - R17W, referenced by:
W. Pine 40 S44W 36 Beech 6 N30W 92

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A5 Oct. 23, 1998 - Thomas P. O'Brien P.S. recovered I.B. with aluminum cap stamped to identify LS 28406. Replaced I.B. with Schoolcraft County Monument stamped to identify.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A5 Schoolcraft County Monument stamped to identify. Established the following references which are blazed, scribed, painted and tagged:

- NBT 14" Maple - N62°W - 127.48'
- NBT 6" R.Pine - N37°E - 83.87'
- NBT 12" W.Pine - S17°E - 72.82'
- (Fd.) 12" J.Pine - S43°E - 39.86'
- Centerline Co. Rd. 455 - West - 15.30'
- Carsonite post - East - 20.0'



Signed by Thomas P. O'Brien
Surveyor's Michigan License No. 21274

Date November 29, 1998