## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	_	,	•
Schoolcraft	Located In:	Corner Code #	
(County)	Located III.	Comer Code #	
1. Public Land Survey	ΤR		
•	TR		
	<u>TR</u>		
2. Property Controlling	S 31 T 41N R 171	<del></del>	
in Section	S 16 T 41H R 171	-	
3. Miscellaneous	S TR		
Property in Sec.	S TR		Register of Deeds Stamp & File Number
4. Lot No, Recor	ded Plat		ABCDEFGHIJKIM
5. Private Claims			1 1 1 1 1 1 1 1 1 1
	-	y 01 2003	2 6 5 4 3 2 1 1
. Stenhan I Szyszkoski		n 03 2003	3
requirements of P.A. 74. Michiga	n a next survey on in P.A. of 1970, the corner po	ints mentioned in lines 1 and 2 above were	der 4 7 8 9 10 11 12
conformance with regulations and	I rules therefore as required in t	the current manual of survey instructions of the	the 5
United States Department of the I that the corner points mentioned	interior, Bureau of Land Manag in lines 3, 4 and 5 above were	pement or by a decree of a Court of Law and a in conformance with the rules of the Michiga	/or 6 19 17 16 15 14 13
Board of Land Surveyors or by	a Decree of a Court of Lav	w; established, re-established, monumente	ed, 7
recovered, found as expressed be	HOW:		8 -19 -20 -21 -22 -23 -24 -
NOTE: Not more than 2 corners, all in the same town and range, may be recorded			9
on this certificate.			10 30 29 28 27 26 25
			11
			12 31 32 34 35 36
A. Description of original mo			13
subsequent record. (2-Sec. 16) East 1/16 corner	between Sections 9 and 3	16. Not established in the original	l survey.
(3-Sec. 31) Found a 5/8" dia accepted same. The corner li	. rebar 0.04'N and 0.04'es approximately 15'east	t of a road.	corner: and Quarter corners north and south and tion corner 1325.82 ft. east and Quarter corner
(3) Set plastic cap "MICH DNR on found 5/8" dia. rebar. Bl scribed, and set measuring na	R PS 33986" (2) Set azed, "MICH Calls in: plastic B" 8" Mapl do 6" Mapl do 6" Elm do 6" Mapl ances are to Center Bearing	established to perpetuate locating the t 5/8"x24" rebar with plastic cap DNR PS 33986". Placed nails with c ID tags in: le S63M 65.9' le S38M 42.6' S37E 44.05' le N11E 41.4' of road is North 2.0' gs are magnetic. Distances are ntal and to nail with tag in the	STEPHAN J. SZYSZKOSKI LAND SURVEYOR No. 33986
Signed by State 1.5	applost side of	f BT. Date	6/16/03