

SCHOOLCRAFT COUNTY
PEER GROUP APPROVED

JAN 2 2000

DATE 11/8/99 JOB LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

Schoolcraft

(County)

Located In:

Corner Code #

SIGRID HEDBERG

SCHOOLCRAFT CO. REGISTER

1P

Page 1 of 1

JL0 Date 12/22/1999

LC 4/304

Time 13:54:15

RECORDING FEES:

9.00

1. Public Land Survey

T^{41N}R^{15W}

G3

2. Property Controlling
in Section

S

T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, thomas P. O'Brien, in a field survey on 11/22, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

Sept.8, 1845 J. Burt, DS set post corner of Sections 3,4,9,10
Aspen 12 N32E 32 B Cherry 6 S50W 20

June 20, 1913 Ernest Weaver, County Surveyor notes "sq. iron pin w/witnesses" in Liber 1
of Record of Surveys, Page 76.

March 8, 1977 Thomas P. O'Brien, PS found monument box 2.3' North of centerline US-2.
May 11, 1978 Douglas W. Hooth, RLS found monument box w/3/4" iron pin MSHD 1939 plans.

Added RLS cap 16944 and witnesses.

Oct.5, 1994 Gary E. Koepke, PS found 3/4" iron w/RLS 16944 cap in monument box.
Added witnesses.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Nov.22, 1999 Thomas P. O'Brien, PS found 3/4" iron in monument box. Split plastic
cap RLS 16944 in bottom of monument box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4" iron bar in monument box

Witnesses:

Power Pole N20°E 64.92'

Drill hole in East end of concrete culvert S55°E 101.33'

x in top of R/W monument S5°W 82.3'

Power Pole N54°W 122.05'

Carsonite Post North 65.0'



Signed by Thomas P. O'Brien

Date 12/16/99

Surveyor's Michigan License No. 21274