SCHOOLCRAFT COUNTY PEER GROUP APPROVED

JAN 2 5 2000

Date 12/16/99	DATE_11/8/9	99 JOB LAN	D CORNER RECORDA	ATION CERTIF	FICATE SECTION	NC
1. Public Land Survey TGIN RISK	For corners in			i 4, MIGH. F.A.	1970	
1. Public Land Survey Tail N 15N Tail N 14N Tail N		Located In:	Corner Code #	SC	HOOLCRAFT CO.REGIS	TER 1P
in Section S T R Property in Sec. S T R 3. Miscollaneous S T R 4. Lot No	•	<u>T_41N</u> R	14W	JLV Date 2 RECORDIN	f 1 12/22/1999 Time G FEES:	LC 4/298 13:52:11
4. Lot No	in Section 3. Miscellaneous	TR S TR S TR S TR			Register of Deeds S	Stamp & File Numb
I. Thomas P. O'Brich, in a field survey on 12/13, 19 99 do hereby state that under requirements of P.A. 74. Moltigam P.A. of 1370, the corner points mentioned in lines 1 and 2 above were in conformance with regulations are not in 1500 as a sequence of the corner banal of survey historication of the that the corner points mentioned in 1500 as a sequence of the corner banal of survey historication of the that the corner points mentioned in 1500 as a sequence of the corner banal of survey historication of the that the corner points mentioned in 1500 as a sequence of a Court of Law above the property of the Mindigan Personal of the Mindigan recovered, found as expressed below. NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate. A Description of original monument and accessories end/or subsequent restoration. Aug. 16, 1845 J. Burt DS set qr. sec. post W Pine N36W 11 W Birch S26W 12 May 21, 1980 Robert E. Schmeling, RLS reestablished corner by proportionate measurement between MI and M3. B. Description of corner evidence found and/or method applied in restoring or reestablehing corner: Dec. 13, 1999 Thomas P. O'Brien, PS recovered pipe w/cap stamped to identify as set by Robert E. Schmeling, RLS. Added additional witness and Carsonite Post. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner. 1" pipe w/brass cap stamped to identify. Witnesses: Thomas P. O'Brien, PS recovered pipe w/cap stamped to identify as set by Robert E. Schmeling, RLS. Added additional witness and Carsonite Post. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner. 1" pipe w/brass cap stamped to identify. Witnesses: Thomas P. O'Brien Date Thomas P	4. Lot No, Record	led Plat				
Description of monument for corner and accessories established to perpetuate locating the position of the corner. 1" pipe w/brass cap stamped to identify. Witnesses: Pine Stump 18" N38°E 28.6' Gedar 8" S74°E 15.9' Gedar 7" S8°W 17.5' Gedar 4" N76°W 12.25' Carsonite POst North 1.0' Thomas P. O'Brien Date 12/16/99	conformance with regulations and r United States Department of the In that the corner points mentioned in Board of Land Surveyors or by a recovered, found as expressed belo NOTE: Not more than 2 come on this certificate. A. Description of original mone Aug. 16, 1845 J. Bu May 21, 1980 Rober	ules therefore as require terior, Bureau of Land M in lines 3, 4 and 5 above a Decree of a Court ow: as, all in the same town in the same tow	er points mentioned in lines 1 and in the current manual of survival anagement or by a decree of a were in conformance with the ref Law; established, re-established and range, may be recorded and range, may be recorded as and/or subsequent restors sec. post W Pine	and 2 above were in the principle of the Court of Law and foules of the Michigar shed, monumented and the court of Law and foules of the Michigar shed, monumented and the court of the cou	3 4	10 -11
Thomas P. O'Brien Thomas P. O'Brien OF Michigan OF Mic	Dec.13, 1999 Thomas	P. O'Brien	PS recovered pipe	17/000 -		set
Date 12/10/99	Vitnesses: Pine Stump 18" N38° Cedar 8" S74°E 15.9 Cedar 7" S8°W 17.5' Cedar 4" N76°W 12.2	stamped to id E 28.6'	ies established to perpetual dentify.	e locating the pos	THE OF MICHIGAN	
	igned by Thomas P. O urveyor's Michigan License No.			Date	12/16/99	