## SURVEY & REMONIJMENTATION

## SCHOOLCRAFT COUNTY PEER GROUP APPROVED

FEB 0 8 2001

DATE 10/10/00 TOB LAND CORNER RECORDATION CERTIFICATE					SECTION						
For corners in	/4, Mich. P.A. 19	70									
Schoolcraft Located In: Corner Code #											
1 Public Land Survey T 42NR 14W K5											
1. Public Land Survey  T 42NR 14W  T R	-										
<u>TR</u>	SIGRID HED	BERG DECRAF	T C	O.RE	GIST	ER		1P			
2. Property Controlling S TR	. Page 1 of JLV Date 1:	1 2/19/2	000	T	ime	LU	4/3 53:	65 14			
in Section S TR				·							
3. Miscellaneous S T R											
, , , , , , , , , , , , , , , , , , ,	-	Reg	ister	of De	eds S	amp	) & F	ile N	umb	er	
4. Lot No, Recorded Plat				ם ה	·	c 1	, T	.7	r	<b>T</b>	
5. Private Claims		1	Ť			G F	1 1	<del>.</del> j	К	Ť	
		3 6		- 5 —	4 		3	-2- 		1-	
, Thomas P. O'Brien, in a field survey on 10/18/00 xes do he	ereby state that under	4 7		- 8-	9			_11_		12-	
requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1	and 2 above were in	5		Ĭ	<u> </u>	لَــــا	Ľ		*	1	
conformance with regulations and rules therefore as required in the current manual of sun United States Department of the Interior, Bureau of Land Management or by a decree of a	Court of Law and /or	6 -18		-17-	16	  -1	5——	 —1,4—	-	 13-	
that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the Board of Land Surveyors or by a Decree of a Court of Law; established, re-established	rules of the Michigan ished, monumented,	7	-				$\vdash$	+	╁	+	
recovered, found as expressed below:		8 -19	+	-2'0	—2'1— 	-2	2	_2'3_ 	+	24-	
NOTE: Not more than 2 corners, all in the same town and range, may be record	led	9		1				+	+	<u>+</u>	
on this certificate.		10 30	`	-29	—28— 	2		-26- 		25-	
		11 12 -31		-32	 33	3	4	 35		-36-	
		13									
April 5, 1851 Algernon Merryweather, DS set sects Beech 9 in N60W 77 links Birch 24 in S50E 59 links. Burch, 1984 William F. Bowman, ILS "set by evidencorners 1 mile North and 2 miles South."	inks		,				ine	s aı	nd .		
B. Description of corner evidence found and/or method applied in restoring of Oct.18, 2000 Thomas P. O'Brien, PS found P.K. fre project. Reset with ½" iron Bar with OBRIEN 21276	om 1998-99 con	rner p	resox.	∋rva	tion	re	sur	face	a)		
•											
C. Description of monument for corner and accessories established to perpet	uate locating the pos	sition of t	ne co	rner							
	*		12880								
iron bar with OBRIEN 21274 cap in monument bow Witnesses: Power Pole N65°W 31.37' 8" Balsam S44°W 83.68' 10" Balsam S53°E 64.20' 8" Balsam N46°E 84.38' Carsonite POst N85°W 30.0'	X. LICENST	THOM. O'BR PROFES: SURVE 212	MICH AS P. EN SION YOR	IGAN AL SONA	Waller Waller						
Olmon D. Ol Su.	**************************************	TOFESS	0NA)	inital.							
Signed by Thomas P. O'Brien	DateDec	c.18,	2000	<u>)                                    </u>							
Surveyor's Michigan License No. 21274											