
LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

_			
For	corn	ore ii	n

5. Private Claims

Schoolcraft	Located In:	Corner Code #
(County)	-	
1. Public Land Survey	T R R T R	
2. Property Controlling in Section	S 21 T 42N R 15W S T R	15 (GCDB 320300)
3. Miscellaneous Property in Sec.	S T R S T R	
4. Lot No. Rec	corded Plat	

Register of Deeds Stamp & File Number



i, Stephan J. Szyszkoski , in a field survey on 08/03/15 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey 5 instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7 the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, a re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(15-Sec. 21) West 1/16 corner between Sections 21 and 28. Not previously monumented.



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(15-Sec. 21) Established the position for the corner midway and on the Section line between Section corner 1316.50' west and Quarter corner 1316.50' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

```
(15) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
21" Hemlock N80°W 36.85'
                                    mrkd "W1/16 BT"
11" Sugar S47°W 8.74'
                                            do
16" Sugar N01°E 8.91'
                                            do
20" Maple S30°E 32.90'
                                            do
E= 8062401.690 N= 136918.575
```

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00 datum. Coord. Ref.=NGS PID DL6164: N= 131822.939 m. E= 8059239.498 m.

Signed by

Date

11/16/2015

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Forest Resources Division