## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended For corners in Schoolcraft Located In: Corner Code # (County) 1. Public Land Survey S<u>28</u> T\_43N K\_ 16W S 28\_ 2. Property Controlling T 43N R 16W in Section S\_28\_ T 43N R 3. Miscellaneous Register of Deeds Stamp & File Number Property in Sec. , Recorded Plat\_ 4. Lot No. 5. Private Claims Stephan J. Szyszkoski in a field survey on Feb. 17 , 20 11 state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below: A. Description of original monument and accessories and/or subsequent restoration: (8-Sec. 28) West 1/16 corner, Section 28. Not established in the original survey. (11-Sec. 28) Southwest 1/16 corner, Section 28. Not established in the original survey. (12-Sec. 28) South 1/16 corner, Section 28. Not established in the original survey. B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: (8-Sec. 28) Established the corner midway and on a straight line between Quarter corner 1324.20' west and the intersection of Quarter lines of Section 28 1324.20' east. (11-Sec. 28) Established the corner at the intersection of straight lines connecting opposite 1/16 corners. (12-Sec. 28) Established the corner midway and on a straight line between Quarter corner 1337.42' south and the intersection of Quarter lines of Sec. 28 1337.42' north. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (8) Set 1"IDx36" I.pipe with 4" Michigan Dept. of (11) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Conservation cap. Set measuring nail/tag in: 12" Cedar S39W 8.5' mrkd "W1/16 BT" Set meas. nail with MDNR tag in the side of: mrkd "W1/16 BT" 5" Tamarack S56W 27.05' mrkd "SW1/16 BT" 7" Cedar N67W 16.35' do 4" Tamarack S83W 30.35 do 7" Cedar N64E 8.4' do 4" Tamarack N07W 51.4' do 6" Cedar S38E 18.4' do 7" J.Pine S22E 78.05' do Set sq. Cedar post adjacent. Bearings are magnetic. Bearings are magnetic. (12) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set meas. nail with MDNR tag in the side of: 16" Cedar S34W 9.15' mrkd "S1/16 BT" OF MICHIO 10" Cedar S85W 3.8' đo 12" Tamarack S61E 15.55' do 9" Cedar N42W 11.4' do STEPHAN J Bearings are magnetic. SZYSZKOSKI LAND SURVEYORD Signed by No. 33986

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources,

11600