

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 8 T 43N R 16W	8
	S 8 T 43N R 16W	11
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Stephan J. Szyszkoski, in a field survey on 8 06/14/2011  
11 05/31/2011 do hereby state  
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2  
above were in conformance with regulations and rules therefore as required in the current manual of survey  
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of  
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with  
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,  
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded  
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 8) West 1/16 corner of Section 8. Not previously monumented.

(11-Sec. 8) Southwest 1/16 corner, Section 8. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 8) Established the position for the corner midway and on a straight line between Quarter  
corner C4 1318.10' west and the Center of Section 8 1318.10' east.

(11-Sec. 8) Established the position for the corner at the intersection of straight lines connecting  
opposite 1/16 corners. The position for the corner falls 1 ft. south of the C/L of an E-W sandy  
woods trail.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.  
Set measuring nail with MDNR tag in the side of:  
10" Maple N26E 6.6' mrkd "W1/16 BT"  
6" Maple N32W 5.75' do  
10" Maple South 22.45' do  
9" Maple S42E 45.7' do  
Bearings are magnetic.

(11) Set 5/8"x18" rebar with plastic MDNR cap  
6" below the surface of an E-W trail.  
Set measuring nail with MDNR tag in the side of:  
5" Maple S56W 9.9' mrkd "SW1/16 BT"  
6" Cedar S56E 28.0' do  
8" J.Pine N67E 33.65' do  
17" W.Pine N12W 40.4' do  
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 02/27/2012

For the Michigan Department of Natural Resources, Forest Resources Division

