

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 22 T 43N R 16W	9
	S 22 T 43N R 16W	13
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, Stephan J. Szyszkoski, in a field survey on 9 06/27/13 do hereby state
13 06/27/13
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(9-Sec. 22) East 1/16 corner, Section 22. Not previously monumented.

(13-Sec. 22) Southeast 1/16 corner, Section 22. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(9-Sec. 22) Established the position for the corner midway and on a straight line between Quarter
corner 1325.32' east and the intersection of Quarter lines of Section 22 1325.32' west.

(13-Sec. 22) Established the position for the corner at the intersection of straight lines
connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(9) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" W.Pine N37°E 3.55' mrkd "E1/16 BT"
15" W.Pine S43°E 55.1' do
11" W.Pine S39°W 42.55' do
8" W.Pine N82°W 16.8' do
E= 8055077.729 N= 147378.488

(13) Set 1"IDx32" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
6" R.Pine S78°W 21.45' mrkd "SE1/16 BT"
6" W.Pine N52°W 18.75' do
13" W.Pine N22°W 44.0' do
12" R.Pine S08°E 12.65' do
E= 8055079.972 N= 146973.295

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum)
Coord. Ref.=NGS PID DL6164: N= 131822.939 m. E= 8059239.498 m.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 08/27/2013

For the Michigan Department of Natural Resources, Forest Resources Division

