

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County) Located In: Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S 11 T 43N R 16W S 12 T 43N R 16W
3. Miscellaneous Property in Sec. S T
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numerical data and a small diagram of a corner point.

I, Stephan J. Szyszkoski, in a field survey on Nov. 7, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration: (9-Sec. 12) East 1/16 corner, Section 12. Not established in the original survey. (7-Sec. 11) North 1/16 corner between Sections 11 and 12. Not established in the original survey.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: (9-Sec. 12) Established the corner midway and on a straight line between Center of Section 1331.75' west and Quarter corner 1331.75' east. (7-Sec. 11) Established the corner midway and on the Section line between Section corner 1317.67' north and Quarter corner 1317.67' south.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: (9) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 6" J.Pine N62E 10.91' mrkd "E1/16 BT" 11" W.Pine N18W 16.65' do 31" W.Pine S29W 28.05' do 33" W.Pine S55E 80.41' do Bearings are magnetic. (7) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: 9" W.Pine N06E 24.35' mrkd "N1/16 BT" 8" W.Pine N65W 10.3' do 15" R.Pine S19W 34.95' do 6" B.Spruce N70E 0.93' do Bearings are magnetic.



Signed by [Signature] Date 11/14/07
Surveyor's Michigan License No. 33986