LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in	#	, man the fore to Amor	· · · · · · · · · · · · · · · · · · ·
Schoolcraft (County)	Located In:	Corner Code#	yi yi
1. Public Land Survey	T R T		
2. Property Controlling in Section	S T R S T R		
3. Miscellaneous Property in Sec.	S 33 T 46N R 13W S T R	PCC South of F11	Register of Deeds Stamp & File Number
4. Lot No. , Re 5. Private Claims	ecorded Plat		A B C D E F G H I J K L I
above were in conformance with instructions of the United States a Court of Law and /or that the	in a field survey on 08/31/30 74, Michigan P.A. of 1970, the corner regulations and rules therefore as required Department of the Interior, Bureau of Licorner points mentioned in lines 3, 4 and 3 of Land Surveyors or by a Decree	points mentioned in lines 1 and 2 ed in the current manual of survey and Management or by a decree of 15 above were in conformance with	6 18 17 16 15 14 13
NOTE: Not more than 2 cor	vered, found as expressed below:	, may be recorded	9 10 30 29 28 27 26 25 11 RR
A Description of original r	monument and accessories and/or	· ·	12 31 32 337 34 35 36
bescription of original i	monument and accessories and/or	subsequent restoration:	1/4 line at N. RRR/w line.
(PCC South of F11) A point on the N-S 1/4 line of Section 33 at its intersection with the northerly R/W line of the Soo Line Railroad. Found no record of prior monumentation.			

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(PCC) Established the position for the corner on a straight line between Quarter corner F11 and Center of Section F12 at its intersection with a line parallel to and offset 50.00' northerly at right angles from the centerline of the existing main line track of the Soo Line Railroad. This position falls 419.52' south of Quarter corner F11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(PCC) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of: Power pole '200-4' N59E 76.7' Sign post N30E 14.3'

Gate post S76W 17.8'

The top bolt of fire hydrant is N70W 89.55'

Bearings are magnetic.

STEPHAN J SZYSZKOSKI LAND RVEYOR AND S

Surveyor's Michigan License No.

Signed by

Date

12/28/2011