

**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft <small>(County)</small>	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S <u>7</u> T <u>46N</u> R <u>13W</u> S _____ T _____ R _____ S _____ T _____ R _____	<u>6</u>
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 04/03/13 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

(6-Sec. 7) Northeast 1/16 corner, Section 7. Not previously monumented.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

(6-Sec. 7) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

(6) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.  
 Set measuring nail with MDNR tag in the side of:  
 5" B.Spruce N15°W 2.95' mrkd "NE1/16 BT"  
 6" B.Spruce S06°E 12.95' do  
 8" Cedar S60°E 41.95' do  
 12" Cedar N66°E 30.15' do  
 E= 8078818.896 N= 180164.916



**Bearings are magnetic.** Coordinates are MCS83 in meters (NAD83(2011) Datum).  
 Coord. Ref.=NGS PID RK0039: N= 173942.810m E= 8064409.357m

Signed by Stephan J. Szyszkoski Date 10/09/2013  
 Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division