

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 19 T 47N R 13W S _____ T _____ R _____ S 19 T 47N R 13W	13 (GCDB 160320) 6
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	(GCDB 160360) _____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

Register of Deeds Stamp & File Number

I, Stephan J. Szyszkoski, in a field survey on 13 9/15/15
6 9/09/15 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(13-Sec. 19) Southeast 1/16th corner Section 19. Not previously monumented.

(6-Sec. 19) Northeast 1/16th corner, Section 19. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(13-Sec. 19) Established the position for the corner at the intersection of straight lines
connecting opposite 1/16th corners.

(6-Sec. 19) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16th corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(13) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:	(6) Set 1"IDx28" I.pipe with 2" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
14" W.Pine S36°W 101.58' mrkd "SE1/16 BT"	7" J.Pine N13°E 24.22' mrkd "NE1/16 BT"
11" Cherry S85°W 52.38' do	7" Cherry N54°E 40.77' do
8" J.Pine N55°E 59.51' do	7" J.Pine S48°W 30.07' do
8" J.Pine N69°E 36.29' do	7" J.Pine N65°W 57.33' do
Set wood post adjacent.	Set wood post adjacent.
E= 8078770.663 N= 185823.849	E= 8078760.562 N= 186631.131

Bearings are magnetic. Coordinates are MCS83 in meters, NAD83(2011) Epoch 2010.00
Coord. Ref.=NGS PID RK0614: N= 185057.887 m. E= 8074174.258 m.

Signed by Stephan J. Szyszkoski Date 11/19/2015
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division, by John Nutkins, PS #52478

