NOV 1 0 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

97 NOV -6 PM 2: 37

REGISTER	OF UEEDS
<i>/</i>	A. Carrier
Baute	Shulla
, -	
SHIAWASSEE	COUNTY MICH.

For corners in

Shiawassee	Located in:	Corner Code #
(County)		
1. Public Land Survey	T_6NR_1E TR TR TR	K-10
Property Controlling In Section	STR STR	
Miscellaneous Property in Sec.	STR STR	

Register of Deeds Stamp & File Number

APPROVED 310010

MARK L

VANRAEMDONCK *

PROFESSIONAL

SURVEYOR

No.

24622

County Remonumentation

Peer Review Group

2

S

ß

8

9 10

11

12

_, Recorded Plat 4. Lot No. 5. Private Claims I, Mark L. VanRaemdonck, in a filed survey on June 11-13, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States

Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this

A. Description of original monument and accessories and/or subsequent restoration:

1. Original Joseph Wampler, DS 3/17/1826 Mon: Wood Post

Access: Elm 13 S13°W 12 LKS Ash 12 N15°W 21 LKS

2. E. S. Brewer, L. C. R. C. Rec. Liber 2, Page 201 11/19/1970

Mon: Set 3/4" Iron pipe on SE side stone Access: Cen 12" Ash 3 feet East

Cen 12" Oak 24.3 feet Northeast Cen 4" Fence Post 21 feet East Cen 4" Fence Post 11 feet South

Centerline of Grand River Road at Sec. Line S01°36'E 712 feet

3. Hathaway J. Hanes, R. L. S. 5260, Cert. Survey, Rec. L. 3, P. 264, Nov. 15, 1979

Mon: 1/2" Re-Iron

Access: Cen 12" Ash 3.0' East Cen 12" Oak 24.3' NE

Centerline Grand River Road on West line Section 25, SO1°36'E 712.00

4. Larry Bryan, P. S. 25832, Cert. Survey, Rec. L. 5, P. 503, 8/15/1988

Mon: Found Large Rock

Access: N&T N. face 18" Elm S80°E 4.45

N&T W. face 18" Twin Elm South 11.10

N&T E. face 8" Aspen N30°W 38.22

5. Larry Bryan, P . S. 25832, Cert. Survey, Rec. L. 5, P. 477, 3/5/1990

Mon: Found Large Rock

Access; N&T N. face 18" Elm S80°E 4.45

N&T W. face 18" Twin Eim South 11.10

N&T E. face 8" Aspen N30°W 38,22

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found 1" Pipe as referenced in No. 2 and No. 3 above. Found large rock (18" more or less in dia.) as referenced in No. 4 and No. 5 above. Offset and removed 1" Pipe. Found ½" pipe, 4 foot long at West side of pipe. Found ½" rerod on East side of 2" pipe removed all. Removed rock, and found no evidence under it. Excavated for Harrison Marker and found rotted wood post 20" below surface. Could not remove the wood post as it probably the remains of an old anchor post. Installed the Harrison Marker over the post at the position of the 1" Pipe. I accepted this location as the original corner position based on the best available

C. Description of monument for corner and accessories to perpetuate locating the position of the corner

Installed a standard Shiawassee County Harrison Marker, stamped "Remon 24622" at the location described above. The marker is witnessed by the

following accessories:

10.14 Found N&T #25832 in W. face Twin 12" Ash South \$20°W 24.13 Found N&T #25832 in W. face 6" Red Oak

3.35 Found N&T #25832 in N. face 18" Ash N35°W 21.21 Found N&T #25832 in East in 5-face 5" Cotton Wood

Date OCT. 30,

Surveyor's Michigan License No. 24622 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS

ORS JAN 18, 197 REVISED MAY 14, 197 REVISED JAN., 198

