

JAN 16 2001

LAND CORNER RECORDATION CERTIFICATE
2000 REMONUMENTATION PROGRAM
Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in

SHIAWASSEE
(County)

Located in:
Venice Twp.

Corner Code



3044411
Page: 1 of 1
12/04/2000 09:53A
L-1 P-351

1. Public Land Survey T 7N R 4E C-2
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

APPROVED
NCC 27 NOV 2000
County Remonumentation
Peer Review Group

4. Lot No. _____ Recorded Plat _____
5. Private Claims _____

I, John H. Rauser, P.S., in a field survey on August 20 00
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

- C-2 1/4 Corner common to Section 5 & 6, T7N-R4E, Venice Township, Shiawassee County
1822 GLO Notes by J. Wampler, D.S., Set wood post, witnessed by N10E 10 lks (6.6') 16" Beech, S40W 30 lks (19.2') 14"
Beech, C-3 to C-2 = 40 ch (2640') C-1 to C-2 = 47.63 ch (3143.58').
1851 County Survey, Book "A", P. 87, Book "B", P. 23 by Monroe Holly, D.S., Monument description-none given, C-2 to B-2=
39.95 ch (2636.7'),
1875 County Survey, Book "C" P. 90, Book "D", P. 84 by Lyman Mason, Monument description-none given,, S66.5E 65 lks (42.9')
12" Lynn,
N63.5W 68 lks (44.88') 10" sugar, C-2 to B-2 = 40.12 ch (2647.92').

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- C-2 1/4 Corner common to Section 5 & 6, T7N-R4E, Venice Township, Shiawassee County
Found two large stones along East side of wood post with smaller stones on West side, approximately 1' below gravel
surface. Excavated to 2.5' found no additional objects. Measured West to B-2 (calculated) = 2647.23', Mason = 2647.92'.
Holley = 2636.70'; measured South to C-3 = 2629.83'. We recommend that the found wood stake be accepted as a careful
and faithful perpetuation of the original government corner and be replaced with a standard Shiawassee County Harrison
monument.

C. Description of monument for corner and accessories established to perpetuate locating the position of the
corner:

- C-2 1/4 Corner common to Section 5 & 6, T7N-R4E, Venice Township, Shiawassee County
Set standard Shiawassee County Harrison monument 0.5' below gravel surface.
S35W 125.77' Set nail & tag #39096 in Northwest face of Power Pole
N30W 42.98' Set nail & tag #39096 in East face of 18" Maple
S85E 35.42' Set nail & tag #39096 in South face of 6" Ash
S50E 39.07' Set nail & tag #39096 in Southwest face of 4" Ash



Signed by John H. Rauser
Surveyor's Michigan License No. 39096

Date 11/09/00