

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

SURVEY &  
 REMONUMENTATION

For corners in

<u>Shiawassee</u> (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>8N</u> R <u>2E</u>	<u>K-9</u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
2. Property Controlling In Section	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
4. Lot No. _____	Recorded Plat _____	
5. Private Claims _____		

NOV 03 1998

SECTION

**Register of Deeds Stamp  
 & File Number**

I, Mark L. VanRaemdonck, in a field survey on June 22, 1998, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

**A. Description of original monument and accessories and/or subsequent restoration:**

- Original, William Brookfield, D.S., December 1823  
 Monument: Wood post  
 Accessories: Hickory 6 N15°E 23  
 Butternut 14 S10°E 29
- Fletcher A. Gould, A.B. Hicks Subdivision, Recorded L 11, page 163, 6/6/55  
 No monument or accessories are given.
- Jack Owens, LCRC recorded L 2, page 454, December 1, 1986  
 Monument: ½" x 18 rerod with YPC #11192 piled stones in mound 7" high x 18" diameter in rocky stream bed.  
 Accessories: West 35.33' Set 40d & flag N face 8" Poplar  
 S30°W 20.18' Set 40d & flag NW face 10" Ash  
 S30°E 29.91' Set 40d & flag W face 8" Poplar  
 N60°E 22.92' Set 40d & flag SE face 14" Hickory  
 West 95.59' Set ½" rerod with YPC #11192 at NE cor. Lot 1, A.B. Hicks Subdivision

**APPROVED**

County Remonumentation  
 Peer Review Group

*NCC 7005 98*

**B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:**

Found rerod and cap #11192 as referenced in No. 3 above. I accepted this location at the careful and faithful re-establishment of the original corner position based on the best available evidence. Found no conflicting evidence.

**C. Description of monument for corner and accessories to perpetuate locating the position of the corner:**

I replaced the rerod and cap with a standard Shiawassee County Harrison Marker Monument, stamped "Remon P.S. 24622" and witnessed by the following accessories:

North	38.57'	Set N&T E face 12" Ash
N60°E	23.00'	Set N&T SE face 24" Hickory
S30°E	30.03'	Set N&T SW face 16" Cottonwood
S30°W	20.16'	Set N&T NW face 16" Walnut

Signed by Mark L. VanRaemdonck

Date SEPT 18, 1998

Surveyor's Michigan License No. 24622

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS JAN 18, 1971  
 REVISED MAY 14, 1975  
 REVISED JAN. 1983



3007696  
 Page: 1 of 1  
 10/27/1998 03:22P

Keye Grubba - Shiawassee Co.

REMON

Lb-1 Pg-249