1996 REMONUMENTATION PROGRAM

1996 REMONUM	ENTATION PROGRAM		# 5 -
	CORDATION CERTIFICATE	20/20	55 로 및 FE
For corners in North Akron Twp.	nt of Act 74, Mich. P.A. 1970	70	
Tuscola Located In: Corner Co	de#		TAKE TAKE
1. Public Land Survey TR		題 (2.1	⇔ P # 6
		Register of Deeds Star	np & File Number
4. Lot No, Recorded Plat			
5. Private Claims	1 A	B C D E F G	HIJKLM
Renneth D. Dunton, in a field survey on Dec. 8, 19 requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned conformance with regulations and rules therefore as required in the current man United States Department of the Interior, Bureau of Land Management or by a country that the corner points mentioned in lines 3, 4 and 5 above were in conformance Board of Land Surveyors or by a Decree of a Court of Law; established, recovered, found as expressed below:	In lines 1 and 2 above were in a bual of survey instructions of the decree of a Court of Law and /or e with the rules of the Michigan re-established, monumented,	-19 -20 -21 -	-3 - 2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
NOTE: Not more than 2 comers, all in the same town and range, may lon this certificate.	be recorded 9	30 20 30	
	11		2/2625
	12	-31 -32 -33 $ -$	34-35-36-
A. Description of original monument and accessories and/or subsequences.	uent restoration:		#0002
Orange Risdon, D.S. Set post on shore of Saginaw Bay. B. Oak 14 S 2 E 44 W. Oak 9 N 63 E 4	June 5, 1885 E. W. Gerrish, Surv Surveyed and laid of of Bay Park. No me set at the meander Line on plat labele road 4 rods wide.	out the Plat of ention of obje- of the Sagina	of the Village ect found or aw Bay.
Note: Section A continued on back o	•		
B. Description of corner evidence found and/or method applied in re	storing or reestablishing corner;		
Found no evidence of post by Risdon 1902 re-survey. Established the cortownship line through Corners A-13 an Risdon's measure of the East line of East line of T14N-R7E, T15N-R7E and July 18 and August 1, 1834.	ner at the westerly d B-13, Tl5N-R8E and Tl4N-R7E. Note:	y extension o nd proportion Risdon measur	f the al to ed the
C. Description of monument for corner and accessories established to	perpetuate locating the position o	f the corner:	•
Set concrete monument with standard N65°E 11.22' set T.C. Remon. tag & s S50°W 23.82' set T.C. Remon. tag & s N89°W 51.77' set T.C. Remon. tag & s N15°W 23.45' set T.C. Remon. tag & s N88°W 40.96' fnd. 5/8" chisel poin West 110'± edge of bay @ marsh grass West 0.5'± Set Carsonite fiber Witness Post	pike in S. face 12' pike in N. face 48' pike in S. face two pike in E. face 15' ted rod in place. & cattails.	" Oak. " triple Cotto in 12" & 15" ; " Oak. (rod is l'± 1	onwood. Poplar.
11 ONAT	S. S	OF MICHIGAN	<u>.</u>
Signed by	Date /2 4	KENHETH D. *	T
Surveyor's Michigan License No. 23503 APPROVED		LAND SURVEYOR	•
12-4-96 J77	FORM APPROVED BY MICHIGAN STATE	NO. 1 67	EVEYORS, JAN. 28, 1971
2.9.8	** <u>*</u> *	POPESSION CONTRACTOR	REVISED MAY 14,1975 REVISED JAN 1983 REVISED OCT., 1995

MAY 2.0 1007 The second second

Sept. 8, 9 & 10, 1902 Survey of Section 36, T15N-R7E by G. B. Felton, County Surveyor. Post at corner 25.73 ch. West of SE cor. Sec. 36. No mention of accessories.

Oct. 9, 1985 Survey by Lionel Roy Emery, L.S. #24593, Liber 554-Pages 897 & 898. Did not establish or use meander corner.

May 12, 1988
Survey by Earl E. Gravlin, L.S. #23510, Liber 585-Pages 1476 & 1477.
Did not establish or use meander corner.

Note: The surveys of 1902, 1985 and 1988 mentioned above, reflect the location of the South line of fractional N 1/2 of fractional SE 1/4 of Section 36, T15N-R7E as occupied.

