

MAR 17 1998

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
SECTION
WAYNE
(County)

Located In:
CITY OF DETROIT

Corner Code # Liber-29744 Page-1028.0
97335335LS 12/22/1997 10:12AM

1. Public Land Survey

T 1S R 12E K-2

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 12-2-97
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

I, MARTIN C. DUNN, in a field survey on NOVEMBER 24, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

UNDER CONTRACT FOR THE GLO ORIGINAL SURVEY

SEPTEMBER 1816

JOSEPH FLETCHER SET A POST

PLATS

L.38 P. 81
L.59 P.29

"GRATIOT LAWN SUBDIVISION"
"GRANGEWOOD GARDENS SUBDIVISION"

7-2-1917
3-12-1926

\$4.00 REMONUMENTATION
RECORDED

FOREST E. YOUNGBLOOD, REGISTER OF
WAYNE COUNTY, MI

Receipt #43579

\$7.00 DEED

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

NO EVIDENCE OF EXISTING CORNER

RE-ESTABLISHED USING A FOUND MONUMENT AND FOUND IRON PIPE ON THE NORTH SIDE OF STATE FAIR, WEST OF SCHOENHERR.
RE-ESTABLISHED SECTION CORNER HOLDING RECORD DISTANCES.
VERIFIED LOCATION WITH OTHER FOUND PIPES ALONG STATE FAIR.

FIELD MEASUREMENTS AND RECORDED DISTANCES

K-2 TO K-1 2637.27 (M) 2637.32 (PLATS) 40 CH. (GLO)
K-2 TO K-3 2654.88 (M) 2654.81 (PLATS) 40 CH. (GLO)
K-1/K-2/K-3 179°52'11" (M)



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
K-2 EAST QUARTER CORNER SECTION 2, T.1S., R.12E., WAYNE COUNTY

PLACED ALUMINUM WAYNE COUNTY REMON CAP W/ #30081 ON 1/2"x18" IRON REBAR WITHIN A NEW MONUMENT BOX IN THE CENTERLINE OF SCHOENHERR AVE.

WITNESSES

67°AZ. 65.30' SET PK NAIL W/ WAYNE COUNTY REMONUMENTATION TAG IN SOUTH FACE OF UTILITY POLE.
108°AZ. 44.64' SET PK NAIL W/ WAYNE COUNTY REMONUMENTATION TAG IN SOUTHWEST FACE OF UTILITY POLE.
214°AZ. 44.71' SET PK NAIL W/ WAYNE COUNTY REMONUMENTATION TAG IN WEST FACE OF UTILITY POLE.
321°AZ. 41.99' SET PK NAIL W/ WAYNE COUNTY REMONUMENTATION TAG IN SOUTHWEST FACE OF UTILITY POLE.

THE SELECTED LOCATION IS A CAREFUL AND FAITHFUL RE-ESTABLISHMENT OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Martin C. Dunn
Surveyor's Michigan License No. 30081

Date 12/5/97