

**SURVEY & REMONUMENTATION**

DEC 02 1993

COMMISSION

**RC 1137**  
**LAND CORNER RECORDATION CERTIFICATE # 26985 PA 928**  
 Filing Requirement of Act 74, Mich. P.A. 1970

93 NOV 24 PM 12:08 RC 1137  
 FOREST COUNTY REGISTERED DEEDS  
 REGISTERED DEEDS  
 REGISTERED DEEDS

For corners in  
**WAYNE**  
 (County)

Located In: Corner Code #

- |                                       |   |    |   |    |     |
|---------------------------------------|---|----|---|----|-----|
| 1. Public Land Survey                 | T | 2S | R | 9E | K-7 |
|                                       | T |    | R |    |     |
|                                       | T |    | R |    |     |
|                                       | T |    | R |    |     |
| 2. Property Controlling in Section    | S |    | T |    | R   |
|                                       | S |    | T |    | R   |
| 3. Miscellaneous Property in Sec.     | S |    | T |    | R   |
|                                       | S |    | T |    | R   |
| 4. Lot No. _____, Recorded Plat _____ |   |    |   |    |     |
| 5. Private Claims _____               |   |    |   |    |     |



Compliance with  
**ACT 345, P.A. 1990**  
 APPROVED ON: 11/24/93  
**WAYNE COUNTY REMONUMENTATION**  
**PEER GROUP COMMITTEE**  
 Register of Deeds Stamp & File Number

I, P.P. Palczynski in a field survey on 4 November, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

**NANKIN TOWNSHIP**

- G.L.O.--(1830'S) DESCRIPTION OF CORNER MONUMENT: ELM 9 DI. COR. TREE. ( NO WITNESSES. )**
- W.P.A.--(1930'S) IRON SET, WITNESSES SHOWN: NEAR COR. BASE CULVERT**
- |                        |        |               |
|------------------------|--------|---------------|
| NE                     | 27.36' | (GONE)        |
| X ON SIGN POST         | SE     | 51.37' (GONE) |
| MANHOLE                | SW     | 28.58' (GONE) |
| NEAR COR. BASE CULVERT | NW     | 27.09' (GONE) |
- NO SUBSEQUENT L.C.R.C. OR C.S. FORMS AT WAYNE CO. REG. DEEDS**

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- FOUND 3/8" REROD IN CONC. MON. IN MONUMENT BOX AT MIDDLEBELT / CHERRY HILL ROADS.**
- MEASURED DISTANCES FOR COMPARISON TO W.P.A. RECORDS:**
- K-7/J-7: W.P.A. = 2542.27' MEAS. = 2542.14'
- K-7/I-7: W.P.A. = 2594.50' MEAS. = 2594.42'
- WAYNE COUNTY ROAD COMMISSION (12-6-89): "MON. IN BOX."**
- |                                |       |        |                |
|--------------------------------|-------|--------|----------------|
| WCRC TAG SW SIDE DE POLE       | 46°NE | 71.67' | (MEAS. 71.67') |
| "X" CUT IN SW BOLT STREET LAMP | 58°SE | 74.32' | (GONE)         |
| WCRC TAG NW SIDE DE POLE       | 47°SW | 71.08' | (MEAS. 71.19') |
| "X" CUT NE BOLT STREET LAMP    | 56°NW | 75.37' | (MEAS. 75.39') |

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- K-7: SECTION CORNER 13, 14, 23, 24 T2S R9E FOUND 3/4" REROD/CONC MON IN MON. BOX. THE SELECTED LOCATION IS ACCEPTED BY THE CONTRACTOR AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER. PLACED W.C. REMON. BRASS MARKER AND CAP "PPP PS 30096".**
- |  |       |        |
|--|-------|--------|
| FOUND PK NAIL/WCRC REF PT TAG IN SE FACE UTILITY POLE. | N40°E | 71.67' |
| SET "X" IN NW BOLT OF TRAFFIC CONTROL TOWER.           | S30°E | 80.89' |
| FOUND PK NAIL/WCRC REF PT TAG IN NW FACE UTILITY POLE. | S37°W | 71.19' |
| WCRC BRASS DISC BM #110-90 - CENTER.                   | S35°W | 79.97' |
| FOUND "X" IN NORTH BOLT OF LIGHT POLE.                 | N50°W | 75.39' |

Signed by [Signature] Date 15 NOVEMBER 1993

Surveyor's Michigan License No. 30096

*2R  
11K D*