\$ 7.00 DEED

Cities	of	inkster	&
Dearb	orn	Height	S

LAND CORNER RECORDATION CERTIFICATE DEC 96 12:43 P.M. Filing Requirement of Act 74, Mich. P.A. 1970 RECORDED TO SECOND FOREST E. YOUNGRLOOD

i P.M. KELE RECORDED

YOUNGBLOOD, REGISTER

WAYNE COUNTY, HI

EDS

For corners in


Compliance with ACT 345, P.A. 1990

APPROVED ON: DEC. 17, 1996
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

	Note that the second of the se	
4. Lot No	Recorded Plat	-
7. LUCITO	, Necolded Flat	
5. Private Claims		_
J. CHVALE CIAILIS	•	

I, <u>LAWRENCE R. FEINDT</u>, in a field survey on <u>OCTOBER 23</u>, 1986 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.



A. Description of original monument and accessories and/or subsequent restoration:

C-10) 1/4 Corner Common to Sections 29 and 30, T 2 S, R 10 E

GENERAL LAND OFFICE SET POST FOR CORNER B. ASH 10"-N47"W-3 LINKS(1.98") B. ASH 12"-S41"E-10 LINKS(6.60") DECEMBER 20, 1816

BY: JOSEPH FLETCHER, DS

WAYNE COUNTY BUREAU OF TAXATION IRON

NW'LY-28.32'-6" ELM GONE SW'LY-33.20'-LIGHT POLE GONE SE'LY-33.82'-LIGHT POLE GONE MICHIGAN STATE HIGHWAY DEPARTMENT
MONUMENT IN BOX
N35°E-56.14'-20" ELM GONE
S55°E-68.20'-NW CORNER BUILDING #2955 FOUND
N30°W-76.67'-12" ELM GONE
APRIL 3, 1964
IRVIN P. MILLER, SURVEY CHIEF

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

C-10) 1/4 Corner Common to Sections 29 and 30, T 2 S, R 10 E

Found concrete monument in monument box 2.0' west of center line of BeechDaly Road. Distance to C-9 measured 2642.62' (WPA=2643.22'). Corner was
confirmed with irons found in "Assessor's Inkster Plat No. 5" as recorded in Liber
65, Page 54, Wayne County records and "Yale Daly Heights Subdivision No. 2" as
recorded in Liber 71, Page 68, Wayne County records.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

C-10) 1/4 Corner Common to Sections 29 and 30, T 2 S, R 10 E

Found concrete monument in monument box 2.0' west of center line of Beech Daly Road. Placed Wayne County brass disk stamped with license #21566 on monument. Road surface is concrete. Corner is accepted as a careful and faithful reestablishment of the position of the original corner.

Witnesses:

N10°W - 134.12' - Found and re-set PK nail with WCR tag in NE side of utility pole

N35°E - 58.17' - "X" cut in top bolt of fire hydrant

S55°E - 67.51' - NW corner of building #2955 (recorded as=68.20')

S65°E - 55.24' - Set nail and WCR tag in SW side of utility pole

S68°W - 57.22' - Found PK nail in SE side of utility pole S70°W - 57.51' - Found PK nail in NW side of utility pole.

4 R

-Signed by Lawrence R. Jonith

December 6, 1996

JP-/

Surveyor's Michigan License No. 21566