

RE-RECORD

\$ 4.00 REMONUMENTATION

For corners in

WAYNE	Located In:
(County)	City of Detroit
1. Public Land Survey	T 2S R 12E
	T R
	T R
	T R
2. Property Controlling in Section	S T R
3. Miscellaneous Property in Sec.	S T R
4. Lot No. _____, Recorded Plat	S T R

Corner Code #

#018

Protracted Location

Seq. 1 Pg 748

Seq. 2 Pg 861

10.00 PAID  
DEC 25 10:25 A.M. RECEIVED  
RECORDED

FOREST E. YOUNGBLOOD, REGISTER

WAYNE COUNTY, MI

28660 PA 861

LIBER 28465 PAGE 748

Compliance with  
ACT 345, P.A. 1990

APPROVED ON: 12-11-95  
WAYNE COUNTY REMONUMENTATION  
FETP GROUP COMMITTEE

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	6	4	3		2		1				
3												
4	7	8	8	10		11		12				
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

City of Detroit

I, George M. Platz, in a field survey on December 8, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:  
Line Common to P.C. 24 and P.C. 248

The western line of P.C. 248 was originally surveyed as one tract of land in 1810. The eastern line of P.C. 248 is adjacent to P.C. 24, which was surveyed as two separate tracts and partially resurveyed in 1825 (see research dossier for sketch and notes). Posts were originally set at the corners of each separate survey and no line stakes are called out. Many subdivisions have been platted adjacent to this line, some delineating it with dimension, others not. The City of Detroit Survey Section has assembled and maintained their "Cartographical Maps" from record plat data and field work. These maps have been relied upon for a great number of years and are considered the best assembled collection of written evidence available. To the best of my knowledge, there has never been any subsequent restoration of this line, excepting the plats which were done long ago.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
Line Common to P.C. 24 and P.C. 248

A complete analysis of this line from its southern beginnings at the Detroit River to its northern terminus just north of Holden Avenue has been field measured by Spalding DeDecker and Associates, locating building lines, street lines and alley lines at various positions (see research dossier). It is my conclusion that a few deflections/line orientation change occur on this line. At this time, I do not have a final answer for the ENTIRE line. The northern and central portions of this line have been determined and the specific points held as good and their relationships with the field measured points are labeled in the research dossier.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
Line Common to P.C. 24 and P.C. 248 -- See sketch on back of this sheet

(E) Set 4"x 36" Concrete Monument w/Brass Disk stamped "WAYNE COUNTY REMONUMENTATION", and Plastic Cap stamped "PS 38121" in a Monument Box Located in the approximate centerline of Brainard St., approximately 120' East of the Easterly R.O.W. line of Lincoln Ave. The centerline of Brainard St. is also the approximate "Rear Line of the Front Concession". The location of this property controlling monument is accepted as a careful and faithful determination of this Private Claim line based upon all known evidence.

Az 37° 37.44'; Set P.K. Nail w/WCR Tag in SE Face of Utility Pole  
Az. 156° 23.16'; Set P.K. Nail w/WCR Tag in NE Face of Guy Pole  
Az. 275° 33.26'; Set P.K. Nail w/WCR Tag in SW Face of Utility Pole  
Az. 334° 13.99'; Chiseled "+" in Top Nut of Fire Hydrant

Signed by George M. Platz  
Surveyor's Michigan License No. 38121

Date 12-11-95

Re - RERECORD TO CORRECT RANGE

Spalding - DeDecker & Assoc. SM94-44 & SM95-28

DPJ

