

FEB 28 1994

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LI 27042 PA 365

For corners in

WAYNE
County:

ROMULUS TOWNSHIP #13 Located in: Corner Code #

1. Public Land Survey T 3 S R 9 E G-03
T _____ R _____
T _____ R _____
T _____ R _____

2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____

3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 12-15-93 *DOJ*
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

RC 1343

I, Kenneth S. Wilkerson in a field survey on October 28, 19 93
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current
manual of survey instructions of the United States Department of the Interior, Bureau of Land Management
or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in
conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law;
established, re-established, monumented, re-monumented, recovered, found as expressed below:

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-03 Set Post - GLO - NO GLO WITNESSES REMAIN
Fd. Iron - B of T
Fd. Iron, L. 21503, P. 273 - 07/27/82

NE 156.32 nail in SE face PP
S 33.38 nail in W face MBT P
S 53.20 nail in E face 16" ash
NW 37.80 nail in SW face PP

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-03 Fd. Iron in mon. box

S 57 E 99.27 X on NW side San. MH Fd
S 7 E 51.25 nail in W face PP Fd
S 1 E 33.55 PK in W face MBT P Fd
S 55 W 62.42 PK in N face 8" cottonwood

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set WC remonumentation washer and OHM KSW 21594 cap on iron.

G-03 N 15 E 51.48 WCRC tag in E face PP
S 55 E 99.43 X on NW side san. MH
S 03 E 51.26 WCRC tag in W face PP
S 05 W 33.58 PK in W face UP

The selected location is accepted as the best evidence of the original corner.

Signed by: *Kenneth S. Wilkerson*

Date: _____

STATE OF MICHIGAN
KENNETH S. WILKERSON
LAND SURVEYOR
REGISTERED LAND SURVEYOR
FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

Drafted By: Kenneth S. Wilkerson
Surveyor's Michigan License No. 21584

Orchard, Hiltz & McCliment, Inc.
34935 Schoolcraft Road * Livonia, Michigan 48150 * Phone: (313) 522-6711

93 DEC 15 PM 5:00
FOREST E. YOUNGLOOD
REGISTERED OF DEEDS
WAYNE COUNTY, MI

*2E
11K*