

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 22 N. R. 9 W.		H-5; H-4;
2. PROPERTY CONTROLLING IN SECTION 10 T. 22 N. R. 9 W.		7; 14
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 3, 1986, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (Continued):

<u>7</u>			<u>14</u>		
Fd. 4" round conc. mon. w/rod;			Fd. 1" pipe; added RLS cap & set		
added cedar post w/loc tag			cedar post w/loc tag		
7" Maple (clp 3)	N25°W	18.0'	8" Red Pine	N55°W	40.9'
12" Maple (clp 2)	N20°E	24.8'	27" Maple (clp 4)	S85°E	23.7'
15" Maple (clp 2)	S55°E	34.7'	33" Red Oak	S55°W	64.2'
Ctr. tr. rd.			Ctr. E-W rd.	Due S	169'
Intersection	S85°W	75'			

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H-5 - Fd. 1½" pipe in monument box; fits 1958 KJO survey on south line of Sec. 10.
H-4 - Fd. & accepted 1" pipe as estab. for ctr. of Sec. 10 at intersection of ¼ lines by Dept. Surveyor Ken Ostling in 1958.
7 - Fd. 4" round conc. monument for N 1/8 Cor. on E. line of Sec. 10. Fits 1958 wits. by Dept. Surveyor Ken Ostling.
14 - Fd. 1" pipe as set by Dept. Surveyor, Ken Ostling in 1958 for S 1/8 cor. on E. line of Sec. 10.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>H-5</u>			<u>H-4</u>		
Fd. 1½" pipe in mon. box in ctr			Fd. 1" pipe; added RLS cap & cedar		
bit. rd. E-W-S & ctr gr. rd. N			post w/loc tag		
Power Pole	N45°E	37.05'	8" Red Oak	N20°W	14.9'
Power Pole	S15°E	117.83'	3" Red Pine	S55°W	37.0'
Telephone Pole	S65°W	75.65'	3" Red Pine	N80°W	30.8'
			4" Maple (clp 2)	N55°W	22.3'

SIGNED BY Carl F. Roser 01-24-86 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

WEXFORD COUNTY