

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Wexford
(County)

Located In

Corner Code #

- | | | | | | |
|--------------------------------------|---|-----|---|-----|---------|
| 1. Public Land Survey | T | 24N | R | 10W | H12 |
| | T | | R | | |
| 2. Property Controlling in Section | S | 34 | T | 24N | R 10W 8 |
| | S | | T | | |
| 3. Miscellaneous Property in Section | S | | T | | R |
| | S | | T | | R |

4. Lot No: _____ Recorded Plat: _____

5. Private Claims: _____

I, Craig W. McVean, in a field survey on July 19, 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

H12 - None

8 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H12 - C 1/4 Corner Sec. 25 - Set stamped 2" Alum. Cap on 5/8" x 34" rebar at intersection of 1/4 line per Standard BLM procedure. Fence corner of fences N & E & W is 7'± North and 3'± West.

8 - CW 1/16 Corner Sec. 34 - Set stamped 2" Alum. Cap on 5/8" x 34" rebar per Standard BLM procedure. Corner of fences N & E & W is 2' South and 3' West.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H12 - Stamped 2" Alum. Cap on 5/8" x 34" long iron rebar. Set Blue Carsonite Post with Loc. Tag 1' NW
N77°W 16.77' to set N & T in N. side 9" S. Maple
N11°W 42.28' to set N & T in W. side 20" S. Maple
East 10.38' to set N & T in N. side 10" S. Maple
S17°W 11.21' to set N & T in E. side 5" S. Maple

8 - Stamped 2" Alum. Cap on 5/8" x 34" long iron rebar. Add Ring of Stones. Set Blue Carsonite Post with loc. tag 1' NE.
N14°E 18.73' to set N & T in W. side 5" S. Maple
N85°E 25.57' to set N & T in N. side 5" S. Maple
South 2.70' to set N & T in W. side 23" S. Maple
S55°W 4.08' to Top center 4' high railroad track iron fence corner.

Signed by:

Craig W. McVean
Surveyor's Michigan License No.: 39088

Date:

11/22/2010