

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. R. 11 W.	1-3, 1-4, 1-5
2. PROPERTY CONTROLLING IN SECTION	T. 24 N. R. 11 W.	14, 16
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E. S. R. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CARL F. ROSER, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on JANUARY 8, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONTINUED)

I-5	16
FD LG B. SPIKE OVER LG IR.	FD IR W/RLS CAP #13030
10" MAPL CLUMP N15°W 62.80	13" CHERRY S60°W 74.74
8" MAPL CLUMP N38°E 68.78	5" MAPLE S30°W 84.50
11" TW MAPL S30°W 30.70	2" W PINE S38°E 94.20
10" W PINE S52°E 86.44	SET CED POST
SET CED POST	W/LOC TAG. NORTH 33'
W/LOC TAG. NORTH 33'	

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- I-3 FD 1" SOLID IR (0.5' DEEP) 0.5'± S OF CTR OF E-W B.TOP ROAD. COR FITS W PINE STUMP REMAINS OF 1915 N.B.T. (MICH CIVIL ENGR & CONST CO) N47°W, 50.3'.
 - I-4 FD IR W/RLS CAP #13030, GLEN DELAMATER WHO FD IR IN 1974. COR IS IN LINE W/FN TO W. COR IS ALSO IN LINE ACROSS FD IR AT POSS CTR OF SEC 11 & FN COR (FN E & N) AT POSS W 1/8 ON E-W 1/4 LINE S-11.
 - I-5 FD LG IR, BADLY BURIED OVER 1 1/2 FT DEEP W/LG B. SPK OVER IT. COR IS 5'± S OF CTR OF E-W GRAVEL RD.
 - 14 FD & ACCEPTED IR W/RLS CAP #13030 FOR NE COR OF SE-SE OF SEC 10. CTR OF E-W TRAIL IS 9'±N. CTR OF N-S TRAIL IS 14'±E.
 - 16 FD & ACCEPTED IR W/RLS CAP #13030 FOR SE COR OF SE-SE OF SEC 10. COR FALLS IN APPROX. CTR OF E-W GRAVEL RD. A N-S FN (NORTH) IS 1'± EAST.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-3	I-4	14
FD 1" SOLID IRON.	FD IR W/RLS CAP #13030.	FD 1/2" IR W/RLS CAP #13030.
16" CHERRY N20°W 55.86	SET CED POST W/LOC TAG.	8" W PINE S84°W 40.09
18" CHERRY S12°E 44.66	17" IRWOOD S70°W 61.50	18" CHERRY S70°E 57.05
4" W PINE N26°E 78.40	18" Y BIRCH S38°W 52.60	6" A PINE N70°E 33.02
10" MAPLE S40°E 68.70	7" W PINE N30°W 52.67	
SET CED POST	20" CHERRY N16°E 76.52	
W/LOC TAG. NORTH 33'		

SIGNED BY Carl F. Roser 01-14-85 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

HANOVER TWP.
WEXFORD COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

