SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in			ad .	
Washtenaw (County)	Located In:	Corner Code #		
1. Public Land Survey	т	R	Coron - 5094735 Page: 1 of 2 82/07/2000 02:	:55P
2. Property Controlling in Section3. Miscellaneous	S T S T	R Peggy M. Haine R R	es - Washtenaw Co. CORREM L-2 P-341 Register of Deed Stam	p & File N
Property in Section	S T		ABCDEFGHI	JKĮ
4. Lot No, Ro	ecorded Plat			
5. Private Claims			2 - 6 + 5 + 4 + 3 +	2 1
			3	1-1-1
			$4 \vdash 7 \vdash 8 \vdash 9 \vdash 10 \vdash$	11 + 12
I, Thomas L. Sutherland	, in a field survey on 11	1-9-1999 do hereby state that	5	
under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the			$\frac{3}{6}$ $\frac{1}{18}$ $\frac{1}{17}$ $\frac{1}{16}$ $\frac{1}{15}$ $\frac{1}{15}$	14 - 1
rules therefore as require	ed in the current manua	of Survey instructions of the	7	+-+-
United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4			8 - 19 + 20 + 21 + 22 +	23 - 2
and 5 above were in con	formance with the rule	s of the Michigan Board of	9	
Land Surveyors or by a monumented, recovered	Decree of a Court of 1 l, found as expressed be	.aw; established, re-established, elow:	10 - 30 + 29 + 28 + 27 +	26 + 2
				P
NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.			12 - 31 + 32 + 33 + 34 +	35 + 3
		sories and/or subsequent resortat	tion: 13	

- A. Description of original monument
 - G.L.O. 1819, Field Notes
 - 1) 8" B.O. S10°E 50 Links
 - 2) 7" Hickory N64°W 18 Links

Continued on Back

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found 1"X24" Iron pipe .7 feet below asphalt surface in center of pavement over a larger pipe 2.7 feet below surface. Set 3/4" x 32" rerod with aluminum recomunmentation cap stamped 24620 in monument box over larger pipe.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3/4"X32" rerod with aluminum remonumentation cap stamped 24620 in monument box over larger pipe 2.7 feet below pavement

- 6) 2' Iron Pipe N20E 33.37
- 8) Power Pole North 31.83 to P.K. on E. Side
- 10) Telephone Jct. Box N73°W 91.9
- 12) Telephone Manhole N81°W 82.85 to Center
- 13) 14" Pine S10°W 41.46 to Remon Tag on W'ly Side
- 14) 16" Pine N52°E 64.05 to Remon Tag on S.E. Side
- 15) 20" Maple S69°W 124.45 to Remon Tag on N.W. Side

I conclude after careful study of the record documentation and field observation, that this corner is accepted as the best available evidence of the position of the original corner.

ITHERLAND.

No. 24G20

Surveyor's Michigan License No.

2000

A. Continued

SECTION

H.H. Atwell #332, No Date, Grid Book Iron Pipe

- 3) 5" Pear S4ºE 21.7
- 4) 5" Apple S26°W 67.9
- 5) 9" Cherry S33°W 25.5
- 6&7) 2 Right of Way Pipes

Washtenaw Engineering, N.N. Fahrner #17620, 5/27/81, L.C.R.C., Liber 6, Page 149; 5/29/81, Survey R-4733; 5/11/83, Survey R-4956; 6/26/85, Survey R-5258; T.L. Sutherland #24620, 6/2/81, Survey R-4735; 1/10/83, Survey R-5039; 5/5/83, Survey R-4951; 8/24/84, Survey R-5123; M.A. Barnwell #33971, 1/5/89, Survey R-5897

- 1" Iron Pipe
- 8) Power Pole N'ly 31.79 to nail
- 9) Fence Post S'ly 33.02 to Nail
- 10) MBT Box N65°W 92.82
- 11) Sign N75ºE 96.9



Paggy M. Haines - Washtenaw Co. CORREM