

## 2001 Alpena County Remonumentation

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970SOUTH 70  
REMONUMENTATION

FEB 01 2002

SECTION

For corners in

Alpena

(County)

Located In:

Corner Code #

## 1. Public Land Survey

T 30N R 07E

M-7

X T 30N R 08E

A-7

T R

T R

S T R

S T R

S T R

2. Property Controlling  
in Section

## 3. Miscellaneous

Property in Sec.

## 4. Lot No. Recorded Plat

## 5. Private Claims

Register of Deeds Stamp &amp; File Number

I, Wayne T. Lewis, in a field survey on 2-24-01, 19X do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

## A. Description of original monument and accessories and/or subsequent restoration:

1839: Lewis Clason set post and witnessed  
 1908: Unknown surveyor for Alpena Co. Road Commission, set large cedar stake in road bed and witnessed  
 1930-1950: Marcus Schaff, P.S., set iron, no witnesses given  
 1973: Alpena Co. Road Comm. found 2" gas pipe and witnessed  
 1977/1980: R.S. Scott (D.B. Guthrie, P.S.) found 1" pipe and raised w/1/2" iron rod, and witnessed  
 1982: E.T. Lewis, P.S., found 1/2" rod and witnessed  
 1988: E.T. Lewis, P.S., found 1/2" rod and witnessed  
 1989: E.T. Lewis, P.S., found 1/2" rod and witnessed  
 1999: Lewis & Lewis (W.T. Lewis, P.S.) found 1/2" rerod w/cap #22435 in mon. box and witnessed  
 1999: Alpena Co. Road Commission found 2" gas pipe with 1/2" rebar, and witnessed

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" rerod w/cap #41922 in mon. box. All witnesses from L&L 1999 W.O. 0403959S check.

This corner is accepted as the best evidence of the location of the original corner.

P.A. 345 ALPENA COUNTY

PEER APPROVED 08-06-01*D. B. T.*

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

2001: Placed 3" Alpena County Remonumentation Cap, stamped to identify the corner, on exist. 1/2" rerod with cap in mon. box

## Witnesses:


East 64.50' 12" Dead Poplar  
 S 67° E 56.75' 12" Pine  
 N 28° W 82.15' 14" Pine  
 S 59° E 69.85' Poplar

Signed by

Surveyor's Michigan License No.

Date

September 14, 2001



L-2 P-369

09/18/2001 08:54A

Page: 1 of 1

Kathy J. Matash, Register Alpena Co., MI LDC 9.00

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
 REVISED MAY 14, 1975  
 REVISED JAN, 1983  
 REVISED OCT, 1995